











RoHS Compliant



US-346

USB 4xRS422/485 1MBaud

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 4 port RS422/485
- USB
- 128 Byte Tx and 384 Byte Rx FIFOs
- Up to 921,600 Baud
- 4xDB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



US-346: USB 4xRS422/485 1MBaud

Description

USB to Serial providing four RS422/485 serial ports. Up to 921,600 data transfer rates and the 128 byte deep transmit and 384 byte receive FIFOS, coupled with 1Mbit line drivers deliver uncompromising performance on your laptop/PC.

USB to serial is the quick low cost way to connect your computer to a serial comms enabled device. Boost software gives industry leading functionality and compatibility.

These products do away with traditional issues with USB technology so you can buy with confidence!

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit and 64 bit editions
- Windows Vista 32 bit and 64 bit editions
- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.





















ORDER Description USB 4xRS422/485 1MBaud **USB Cable & Power Supply**

Code US-346



USB 4xRS422/485 1MBaud

US-346: Full Specification

| D. I | Ports | 4 x RS422/485 |
|-------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Port | | |
| Pin 1 TXD- Pin 2 TXD+ | Connector | 4xDB9 connector (9 Pin Male) |
| Pin 3 RTS- Pin 4 RTS+ | FIFO size | 384 RX FIFO + 128 TX FIFO |
| Pin 5 GND Pin 6 RXD- | Operating Distance | RS422/485 Standard (4000 ft : 1200 metres) |
| Pin 7 RXD+ Pin 8 CTS- Pin 9 CTS+ 6 9 | Cable | USB Cable |
| | | (Powered via industrial locking connector with 5V 3A power adaptor - supplied) |
| Port Settings | Baud Rate | 921,600 |
| 921,600 | Data Bits | 7 or 8 |
| >>> >> | Parity | Odd, Even, None, Mark or Space |
| baud | Stop Bits | 1 or 2 |
| | Flow Control | RTS/CTS, XON/XOFF |
| | Tx/Rx Modes | Full Duplex, Half Duplex Autogating |
| Interface | OS Compatibility | Microsoft Windows 7 32bit & 64bit Editions Windows Vista 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions |
| | BUS | USB: |
| Approvals | Other Approvals | WEEE RoHS EMC: CE Microsoft Certified Gold Partner |
| ROHS CE | Microsoft Approvals | Microsoft Certified Gold Partner |
| General | PCB Layers | 4 |
| | Power Consumption | 500mA |
| | Weight | 0.650 Kg |
| | Size | 215x32x120 mm |
| Box Content | Packaging | Installation CD (including manual, Microsoft signed drivers & utilities |
| | Card | USB 4xRS422/485 1MBaud |
| Product Support | Warranty | Lifetime (online registration required) |
| | Support | Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team |
| Additional | OEM option | Available for bulk buy OEM |
| Elektra O5 | Made In | Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year" |
| WINNER Manufacturer of the Year Made in the UK | Customisable | Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com |

Datasheet Version: 4.37 Published on: 2009/12/17