Rittal RiCase accessories



Mounting angles 482.6 mm (19 ")

For front/rear installation of subracks and blanking plates.

Material:

Extruded aluminium section, clear-chromated

Supply includes:

Assembly parts.

Note:

1 pack of tapped strips and 2 packs of mounting rails and spacers are required for depth-adjustable installation.

Model No. RC	Packs of	For enclosure height
3751.650	2	1 U
3751.660	2	2 U
3751.670	2	3 U
3751.680	2	4 U
3751.690	2	6 U
3751.640	2	7 U
3751.780	2	9 U
3751.790	2	12 U



Slide-in strips, see page 564. Mounting rails, see page 564. Spacers, see page 564.



Threaded inserts

with M4 thread for RiCase, Vario-Case iS

For the installation of mounting brackets, slide rails, mounting kits, cable ducts etc. Simply slide into the channels in the side panels.


Material:

Extruded aluminium section, clear-chromated

Model No. RC	Packs of	For enclosure height
3751.700	8	1 U
3751.710	8	2 U
3751.720	8	3 U
3751.730	8	4 U
3751.740	8	6 U
3751.750	8	7 U
3751.760	8	9 U
3751.770	8	12 U

В





В

С

Mounting rails

- For depth-variable installation of mounting angles
- For the installation of component shelves, static or pull-out

Material:

Aluminium, clear-chromated

Supply includes:

- Assembly parts.
- A Version for depth-variable mounting angles
- B Component shelf installation for 482.6 mm/19" (width 409 mm, also with telescopic slides)
- C Direct component shelf installation (width 471 mm)

1 Slide-in strips

- 2 Short spacers
- 3 Long spacers
- 4 Mounting rails

For enclosure depth mm	Packs of	Model No. RC
420	2	3751.410
540	2	3751.420

Also required:

Threaded inserts, see page 564. Spacers, see page 564.

+ Accessories:

Component shelf, see page 944. Component shelf, 482.6 mm (19"), see page 939.



Spacers

For the attachment of mounting rails.

Version	Packs of	Model No. RC
Short for depth-variable mounting bracket	4	3751.450
Long for component shelf installation (width 409 mm)	4	3751.460

Α