

Techniseal Self adhesive foam sealants



Features:

- Cushioning.
- Sound insulation.
- Water seals.
- Air seals.
- Dust seals.
- Light seals.
- Abrasive protection.
- Electrolytic insulation.
- Draught seals.
- Anti-vibration insulation.
- Security bonding.

Medium density PVC foam air, dust and weatherseal, coated on the face side with an acrylic pressure sensitive adhesive for easy positioning. A removable support liner on the other side prevents stretch during application. For general sealing and cushioning applications, can be cleanly drilled through for mechanical fixing.

Width : 6 to 1400mm.
Thickness : 3, 4.5 and 6mm.
Colours : Black (TSB 220), White (TSW 220) and Gray (TSG 220).

Part Number Table

Description	Part Number
Tape foam sealer	Techniseal 220

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC pro-Power is the registered trademark of the Group. © Premier Farnell plc 2010.