








## Relieved Head

### Length 110 mm


Model	L	A	B	C	Max. Cu	Weight	Description
 <p>676E</p>	110 mm	9 mm	9 mm	6 mm	∅ 1,0 mm	48 g	<p><b>Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable</b></p> <p>Miniature side cutter. Super fine relieved head allows very good access.</p>
 <p>776E</p>	110 mm	9 mm	9 mm	6 mm	∅ 1,0 mm	48 g	<p><b>Super full flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable</b></p> <p>Miniature side cutter. Super fine relieved head allows very good access. Soft wires only.</p>
 <p>632NCF</p>	110 mm	9 mm	9 mm	6 mm	ask for cutting capability*	48 g	<p><b>Super full flush cut, high grade tool steel, anti-glare finish, ESD safe, soft materials only</b></p> <p>Miniature side cutter. Special fine, high precision cut exclusively designed for soft materials like small Silicone tubing in medical applications, precision connector sealing, miniature rubber gaskets or cutting of molded soft synthetic parts. Super fine relieved head allows very good access.</p>

\* Please provide wire sample.

### Length 115 mm

Model	L	A	B	C	Max. Cu	Weight	Description
 <p>576Z</p>	115 mm	9 mm	10,5 mm	6,5 mm	∅ 1,2 mm	67 g	<p><b>Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable</b></p> <p>Side cutter with fine relieved head. Medium size. For fine wires.</p>
 <p>592E</p>	115 mm	12 mm	10,5 mm	6,5 mm	∅ 0,6 mm	67 g	<p><b>Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable</b></p> <p>Side cutter with relieved head. Medium size. For Copper wires.</p>
 <p>576TX</p>	115 mm	11 mm	10,5 mm	6,5 mm	ask for cutting capability*	67 g	<p><b>Flush cut, Tungsten Carbide blades, anti-glare finish, ESD safe</b></p> <p>Miniature side cutter. Super fine relieved head allows very good access. Tungsten Carbide blades for constant quality cuts. Resistant to small stainless steel wires.</p>
 <p>792E</p>	115 mm	13 mm	10,5 mm	6,5 mm	∅ 0,6 mm	67 g	<p><b>Super full flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable</b></p> <p>Side cutter with relieved head. Medium size. For fine soft wires.</p>

### Length 120 mm

Model	L	A	B	C	Max. Cu	Weight	Description
 <p>884E</p>	120 mm	15 mm	13,5 mm	7,5 mm	∅ 1,8 mm	81 g	<p><b>Flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable</b></p> <p>Side cutter for large wires.</p>