



Rubber Grommet Rutaseal EPDM Metric



Material:

EPDM

Resistant to chemicals and weatherproof.

Suitable for holes in materials of 0,5 - 4mm thickness.

Quick and simple assembly without the use of tools.

IP67 acc. to EN 60529

-30°C....+130°C

SEMKO 44:1984

0211038/01-07



Mode of protection:

Temperature range:

Test standard:

Semko report:

Halogen-Free




 **RAL 7001**
Grey

E-number Art.no	Size	For cable Ø mm	A mm	B mm	Da mm	H mm	H1 mm	Colour	Weight/ 100pcs	Pcs pack
14 582 33	M12	4-7	12,5	0,5-2	20,0	12,8	5,6	RAL 7001	0,35	50
14 582 34	M16	5-9	16,5	1-4	21,0	17,7	11,0	RAL 7001	0,45	50
14 582 35	M20	8-12	20,5	1-4	25,5	20,0	13,4	RAL 7001	0,71	50
14 582 36	M25	11-16	25,5	1-4	30,5	21,3	15,3	RAL 7001	1,02	50
14 582 37	M32	15-20	32,5	1-4	38,5	24,6	18,6	RAL 7001	1,72	25
14 582 38	M40	19-28	40,5	1-4	48,5	29,5	21,7	RAL 7001	3,28	25
14 582 39	M50	27-35	50,5	1-4	60,5	34,8	25,0	RAL 7001	4,97	10

 **RAL 9005**
Black

14 582 93	M12	4-7	12,5	0,5-2	20,0	12,8	5,6	RAL 9005	0,35	50
14 582 94	M16	5-9	16,5	1-4	21,0	17,7	11,0	RAL 9005	0,45	50
14 582 95	M20	8-12	20,5	1-4	25,5	20,0	13,4	RAL 9005	0,71	50
14 582 96	M25	11-16	25,5	1-4	30,5	21,3	15,3	RAL 9005	1,02	50
14 582 97	M32	15-20	32,5	1-4	38,5	24,6	18,6	RAL 9005	1,72	25
14 582 98	M40	19-28	40,5	1-4	48,5	29,5	21,7	RAL 9005	3,28	25
14 582 99	M50	27-35	50,5	1-4	60,5	34,8	25,0	RAL 9005	4,97	10

 **White**

14 583 13	M12	4-7	12,5	0,5-2	20,0	12,8	5,6	White	0,35	50
14 583 14	M16	5-9	16,5	1-4	21,0	17,7	11,0	White	0,45	50
14 583 15	M20	8-12	20,5	1-4	25,5	20,0	13,4	White	0,71	50
14 583 16	M25	11-16	25,5	1-4	30,5	21,3	15,3	White	1,02	50
14 583 17	M32	15-20	32,5	1-4	38,5	24,6	18,6	White	1,72	25
14 583 18	M40	19-28	40,5	1-4	48,5	29,5	21,7	White	3,28	25
14 583 19	M50	27-35	50,5	1-4	60,5	34,8	25,0	White	4,97	10