









RoHS Compliant



US-279

USB2Serial 8xRS232

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 8 port RS232
- USB to Serial
- 128 Byte Tx and 384 Byte Rx FIFOs
- Up to 921,600 Baud
- 8xDB9 connector (9 Pin Male) Industrial high retention USB connector
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



US-279: USB2Serial 8xRS232



Description

USB to Serial providing 8 RS232 serial ports. Up to 921,600 data transfer rates and the 128 byte deep transmit and 384 byte receive FIFOS, coupled with 1Mbit line drivers deliver uncompromising performance on your laptop/PC.

USB to serial is the quick low cost way to connect your computer to a serial comms enabled device. Boost software gives industry leading functionality and compatibility.

These products do away with traditional issues with USB technology so you can buy with confidence!

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Vista 32 bit and 64 bit editions
- Windows XP 32 bit & 64 bit editions



As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.



















ORDER
Description
USB2Serial 8xRS232

Code US-279

US-279



USB2Serial 8xRS232

US-279: Full Specification

Port	Ports	8 x RS232
	Connector	8xDB9 connector (9 Pin Male)
Pin 1 DCD RS232 Pinout (9 pin Male)		USB Type B High Retention
Pin 2 RXD 1 5 Pin 3 TXD	FIFO size	384 RX FIFO + 128 TX FIFO
Pin 4 DTR Pin 5 GND Pin 6 DSR	Operating Distance	EIA - RS232 Standard
Pin 6 USK Pin 7 RTS Pin 8 CTS Pin 9 RI 6 9	Cable	USB Cable
		(Powered via industrial locking connector with 5V 3A power adaptor - supplied)
Port Settings	Baud Rate	921,600
021 600	Data Bits	7 or 8
921,600 > > >	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1 or 2
	Flow Control	RTS/CTS, DTR/DSR, XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Windows Vista 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions
	BUS	USB to Serial :
Approvals	Other Approvals	WEEE ROHS EMC: CE Microsoft Certified Gold Partner
ROHS CE	Microsoft Approvals	Microsoft Certified Gold Partner
General	PCB Layers	4
	Power Consumption	600mA @ 5V
	Weight	0.0 Kg
	Size	0x0x0 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	USB2Serial 8xRS232
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 2.77 Published on: 2009/5/26