

Belden Wire & Cable - Multi-Conductor Cable

Audio and Control Cable  
Overall Beldfoil® Shield  
22 AWG, 1 Pair  
Single and Double Pair

Trade Number: 8451

NEC CM  
CEC CM

Conductor AWG: 22  
Conductor Stranding: (7x30)  
Conductor Type: TC

Insulation Type: Polypropylene  
Insulation Thickness: 0.008 in.

Jacket Type: PVC  
Jacket Thickness: 0.02 in.

Shield Type: Beldfoil

Nominal OD: 0.138 in.

Nominal Capacitance: 34 pF/ft\*  
Nominal Capacitance: 67 pF/ft\*\*

**Standard Lengths(ft.) Standard Units(lbs.)**

100	1.7
250	3.5
U-500	7.4
500	7
U-1000	13.8
1000	13.5

**DESCRIPTION**

Tinned copper, polypropylene insulated, twisted pair. Beldfoil® aluminum-polyester shield, 22 AWG solid tinned copper drain wire. Paper wrap. Gray or Black PVC jacket. Belden's® Miniature Type Broadcast Audio and Instrumentation Cables occupy 1/2 to 2/3 less space than standard cables. Suggested working voltage: 300V RMS. Beldfoil® 100% Shield coverage. 105°C.

Color code: Black, Red.

\*Capactiance between conductors.

\*\*Capacitance between one conductor and other conductors connected to shield.