

May 16, 2008

Re: Lexa Splash Goggle Gear

AOSafety Lexa Splash Goggle Gear has been tested to and meets the requirements specified in the American National Standard, ANSI Z87.1 – 2003 for goggles. Among the tests are:

Drop Ball Impact: Basic impact goggles shall be capable of resisting impact from a 22 mm (7/8 inch) diameter steel ball weighing 44.2 g (1.56 oz.) dropped from a height of 1.0 m (39.0 inches) onto the center of the horizontal outer surface of the lens. The lens shall not fracture or be pierced as a result of this test.

Basic impact goggles shall be capable of resisting penetration from a pointed projectile consisting of a new 135 X 17 needle fastened into a holder weighing 44.2 gm (1.56 oz.) dropped from a height of 127 cm (50.0 inches) onto the center of the horizontal outer surface of the lens. The lens shall not fracture or be pierced as a result of this test.

The lenses shall be free of striae, bubbles, waves, and other visible defects and flaws which would impair their optical quality.

Lexa Splash Goggle Gear also complies with the Canadian National Standard CSA Z94.3.

Aearo Company is an ISO9001 registered facility and we make every effort to supply our customers with a quality product.

Ann L Phillips

Quality Assurance Manager

(dund. Phillis