

BENCH MODELS												
Model No	Type	Regulation	O/Ps	Main Output(s)	Aux. Output	Power	Fan	OVP	Controls	Meters	Size mm	Weight
EB2025T	Basic	Linear	Triple	0.3 - 20V / 0 - 0.25A	5V @ 1A	15W			Analogue	Analogue	220x82x230	1.8kg
EL301R	Precision	Linear	Single	0 - 30V / 0 - 1A		30W			Analogue	LED	140x160x195	3.4kg
EL183R	Precision	Linear	Single	0 - 18V / 0 - 3.3A		60W			Analogue	LED	140x160x195	4.4kg
EL302R	Precision	Linear	Single	0 - 30V / 0 - 2A		60W			Analogue	LED	140x160x195	4.4kg
EL561R	Precision	Linear	Single	0 - 56V / 0 - 1.1A		60W			Analogue	LED	140x160x195	4.4kg
EL155R	Precision	Linear	Single	0 - 15V / 0 - 5A		75W			Analogue	LED	140x160x195	5.0kg
EL303R	Precision	Linear	Single	0 - 30V / 0 - 3A		90W			Analogue	LED	140x160x195	5.0kg
EL302RD	Precision	Linear	Dual	0 - 30V / 0 - 2A		120W			Analogue	LED	260x160x195	7.5kg
EL302RT	Precision	Linear	Triple	0 - 30V / 0 - 2A	1.5 - 5V @ 2A	130W			Analogue	LED	260x160x195	7.5kg
EX1810R	Precision	Mixed Mode	Single	0 - 18V / 0 - 10A		180W			Analogue	LED	140x160x195	3.0kg
EX355R	Precision	Mixed Mode	Single	0 - 35V / 0 - 5A		175W			Analogue	LED	140x160x195	3.0kg
EX2020R	Precision	Mixed Mode	Single	0 - 20V / 0 - 20A		400W	•		Analogue	LED	140x160x195	3.5kg
EX4210R	Precision	Mixed Mode	Single	0 - 42V / 0 - 10A		420W	•		Analogue	LED	140x160x195	3.5kg
EX354RD	Precision	Mixed Mode	Dual	0 - 35V / 0 - 4A		280W			Analogue	LED	260x160x195	4.3kg
EX354RT	Precision	Mixed Mode	Triple	0 - 35V / 0 - 4A	1.5 - 5V @ 5A	305W			Analogue	LED	260x160x195	4.3kg
EX752M	Compact	Mixed Mode	Dual **	0 - 75V / 0 - 2A		300W			Analogue	LED	260x160x195	4.4kg
PL155	Precision	Linear	Single	0 - 15V / 0 - 5A		75W		•	Analogue	LED	105x130x295	4.5kg
PL303	Precision	Linear	Single	0 - 30V / 0 - 3A		90W		•	Analogue	LED	105x130x295	4.5kg
PL601	Precision	Linear	Single	0 - 60V / 0 - 1.5A		90W		•	Analogue	LED	105x130x295	4.5kg
PL303QMD	Precision	Linear	Dual *	0 - 30V / 0 - 3A		180W		•	Analogue	LED	210x130x295	9.0kg
PL154	Precision	Linear	Single	0 - 15V / 0 - 4A		60W			Analogue	LED	155x170x265	5.0kg
PL320	Precision	Linear	Single	0 - 32V / 0 - 2.1A		65W			Analogue	LED	155x170x265	5.0kg
PL330	Precision	Linear	Single	0 - 32V / 0 - 3.1A		95W			Analogue	LED	155x170x300	6.0kg
PL320QMD	Precision	Linear	Dual *	0 - 32V / 0 - 2.1A		130W			Analogue	LED	350x170x265	9.5kg
PL330QMD	Precision	Linear	Dual *	0 - 32V / 0 - 3.1A		190W			Analogue	LED	350x170x300	12.0kg
PL320QMT	Precision	Linear	Triple *	0 - 32V / 0 - 2.1A	4 - 6V / 0 - 4A	155W			Analogue	LED	425x170x265	13.5kg
PL330QMT	Precision	Linear	Triple *	0 - 32V / 0 - 3.1A	4 - 6V / 0 - 7A	230W			Analogue	LED	425x170x300	15.5kg
TS3021S	Precision	Linear	Single	0 - 30V / 0 - 2A		60W			Analogue	LCD	160x160x238	4.9kg
TS3022S	Precision	Linear	Dual	0 - 30V / 0 - 2A		120W			Analogue	LCD	308x160x238	9.6kg
QL355	High Precision	Linear	Single	0 - 35V / 0 - 5A #		105W	•	•	Digital	LED	141x171x300	5.0kg
QL564	High Precision	Linear	Single	0 - 56V / 0 - 4A #		112W	•	•	Digital	LED	141x171x300	5.0kg
QL355T	High Precision	Linear	Triple	0 - 35V / 0 - 5A #	2.7V-5V @ 1A	215W	•	•	Digital	LED	282x171x300	10.0kg
TSX1820	Precision	Mixed Mode	Single	0 - 18V / 0 - 20A		360W		•	Analogue	LED	210x130x350	5.0kg
TSX3510	Precision	Mixed Mode	Single	0 - 35V / 0 - 10A		350W		•	Analogue	LED	210x130x350	5.0kg
CPX200	Precision	PowerFlex	Dual	0 - 35V / 0 - 10A †		350W		•	Analogue	LED	210x130x350	6.0kg
CPX400A	Precision	PowerFlex	Dual	0 - 60V / 0 - 20A †		840W	•	•	Analogue	LED	210x130x350	7.5kg
BUS PROGRAMMABLE MODELS												
Model No	Interfaces	Regulation	O/Ps	Main Output(s)	Aux. Output	Power	Fan	OVP	Local Cntrl	Meters	Size mm	Weight
EL302-P	RS-232	Linear	Single	0 - 30V / 0 - 2A		60W			Digital	LED	140x160x195	4.4kg
EX355-P	RS-232	Mixed Mode	Single	0 - 35V / 0 - 5A		175W			Digital	LED	140x160x195	3.0kg
PL155-P	RS-232/USB/LAN	Linear	Single	0 - 15V / 0 - 5A		75W		•	Analogue	LED	105x130x295	4.7kg
PL303-P	RS-232/USB/LAN	Linear	Single	0 - 30V / 0 - 3A		90W		•	Analogue	LED	105x130x295	4.7kg
PL601-P	RS-232/USB/LAN	Linear	Single	0 - 60V / 0 - 1.5A		90W		•	Analogue	LED	105x130x295	4.7kg
PL303QMD-P	RS-232/USB/LAN	Linear	Dual *	0 - 30V / 0 - 3A		180W			Analogue	LED	210x130x295	9.2kg
PL330-P	RS-232 & GPIB	Linear	Single	0 - 32V / 0 - 3.1A		95W			Analogue	LED	207x170x300	6.5kg
PL330D-P	RS-232 & GPIB	Linear	Dual	0 - 32V / 0 - 3.1A		190W			Analogue	LED	350x170x300	12.5kg
PL330T-P	RS-232 & GPIB	Linear	Triple	0 - 32V / 0 - 3.1A	4 - 6V / 1 - 7A	230W			Analogue	LED	425x170x300	16.0kg
QL355-P	USB/RS232/GPIB	Linear	Single	0 - 35V / 0 - 5A #		105W	•	•	Digital	LED	141x171x300	5.0kg
QL564-P	USB/RS232/GPIB	Linear	Single	0 - 56V / 0 - 4A #		112W	•	•	Digital	LED	141x171x300	5.0kg
QL355T-P	USB/RS232/GPIB	Linear	Triple	0 - 35V / 0 - 5A #	2.7V-5V @ 1A	215W	•	•	Digital	LED	282x171x300	10.0kg
TSX1820-P	RS-232 & GPIB	Mixed Mode	Single	0 - 18V / 0 - 20A		360W		•	Digital	LED	210x130x350	5.5kg
TSX3510-P	RS-232 & GPIB	Mixed Mode	Single	0 - 35V / 0 - 10A		350W		•	Digital	LED	210x130x350	5.5kg
QPX1200	RS-232/USB/LAN	PowerFlex	Single	0 - 60V / 0 - 50A †		1200W	•	•	Digital	LCD	350x130x 415	9.2kg

Changes and Additions marked
in **RED**