

## ESD Refuse Sack

### Features:

- Our ESD refuse sacks are made of antistatic polyethylene
- Printed in black with ESD caution logo and text onto polyethylene
- Supplied in packs of 100
- Available in either blue, yellow or clear from stock

Homogeneous, non-amine antistatic polythene film which is effective at low relative humidities (less than 12%).

Specifically designed for the particular needs of the electronics industry, it meets Type II Mil B 81705C.

The special additives used do not effect the film clarity or quality, and it is therefore most economical in use, as the standard film thickness can be selected.



### Technical Specifications:

Technical Properties:	Details:
Thickness	130 Gauge – 32.5 Microns
Tensile Strength (ASTM D 882)	1500 to 3000 psi
Tear Strength (ASTM D 1004)	65 to 450lbs/inch
Elongation (ASTM D 882)	MD: 550
Dart Impact (ASTM D 3420)	250-750 grms
Burst (Mullen) (ASTM D 3420)	20 – 60 psi
Heating Sealing (ASTM D 882)	Temperature: 250-375°F
Time	.25 – 3.5 seconds
Pressure	30-60 psi
Electrical Properties:	
Surface Resistivity	(Inside/Outside) at 28.8°C and 12% RH < 1011ohms/sq
Static Decay Rate	(5000 volts O volts at 28.8°C and 12% RH) <2 seconds

Product Code:	Description:	Size:	Additional Notes:
1812584	ESD Bin Liners - Blue	110 Litre	Pack of 100 (Ref: 091-0028)
1812585	ESD Bin Liners - Yellow	110 Litre	Pack of 100 (Ref: 091-0036)
1812586	ESD Bin Liners - Clear	110 Litre	Pack of 100 (Ref: 091-0046)

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, a ny error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2008.