cable

4	P.C.
-	-
COMPAN	Y PROFILE



MANUFACTURING

1.0



LIGHTING

2000-

CONNECTORS

ASSELECTION OF A STREET, STR

PATCHING



RACKING





CABLE ACCESSORIES



VAN DAMME





INDEX





Flexible universal Scart cable for the combined transmission of audio, video and data signals in one cable. Only available on 25m reels. For use with Scart connectors on page 297.

VC de e	Grand	Conductor	10.01		
Video	Construction	Conductor	10x0.1mm stranded		
(6x75 Ohm core	s)		plain copper 26AWG		
		Insulation	Foamed polyetheylene		
		Screen	Lapped 0.1mm plain co	pper	
		Sheath	Polyethylene		
		Core colours (1 each)	Green, red, yellow, blac	k, blue & v	vhite
Audio (4 cores)	Construction	Conductor	10x0.1mm stranded pla	in copper 2	6AWG
		Insulation	Polyethylene		
		Screen	Aluminium/ polyester fo	il with	
			tinned copper drain wire	3	
		Core colours (1 each)	Red, white, yellow & bla	ack all in gr	ey jacket
Data (4 cores) Construction		Conductor	10x0.1mm stranded pla	in copper 2	6AWG
		Insulation	Polyethylene		
		Core colours	Red, white, yellow & blu	Je	
Jacket	PVC				
Nominal OD	10.4 mm				
Jacket colour	Black				
Maxreel size	25m				
Weight	5kg				
Overall Construct	tion 6 video, 4 audio	and 4 data cores overall sc	reened with aluminium/po	lyester foil	with a
	tinned copper dra		, , , , , , , , , , , , , , , , , , ,	,	
Stock code Description			1+	5+	10+

(9	
()	U