

UUSB-AB-S-S-SM-TR

UUSB-B-S-F-SM-TR

MUSB-05-S-AB-SM-A

MUSB, MUSBR, UUSB SERIES

MINI & MICRO USB 2.0 INTERFACES

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?MUSB, www.samtec.com?MUSBR-A or www.samtec.com?MUSBR-B

Insulator Material:

High Temperature Thermoplastic

Contact Material:

Phosphor Bronze

Shell Material:

Brass

Plating:

Gold on Mating Area, Nickel on Shell, Tin on Tails

Operating Temp Range:

-50°C to +85°C

Current Rating:

1A per contact

Voltage Rating:

30 VRMS

Contact Resistance:

50 mΩ max

Minimum Cycles:

1500

Packaging:

Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are available upon request.

RoHS Compliant:

Yes

Lead-Free Solderable:

Yes

TYPE

MUSB
= Mini USB 2.0

MUSBR
= High Retention Mini USB 2.0

NO. OF CONTACTS

-05

PLATING

-F
= Gold Flash on Mating Area, Tin on Tails

-S
= 30μ" (0,76μm) Gold on Mating Area, Tin on Tails

COLOR

Leave blank for MUSB
-O
= Orange

TYPE





-B
= B Type (MUSB & MUSBR)

-AB
= AB Type (MUSB only)

-A
= A Type (MUSBR only)

ALSO AVAILABLE

Mini USB-A Type.
Call Samtec.



SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?UUSB-AB or www.samtec.com?UUSB-B

Insulator Material:

Black LCP

Contact Material:

Phosphor Copper

Plating:

Au over 50μ" (1,27μm) Ni

Shield Plating:

Sn over 50μ" (1,27μm) Ni

Operating Temp Range:

-30°C to +80°C

Current Rating:

1A (pin 2, 3, 4)

per signal contact,

1.8A (pin 1, 5)

per power contact

Voltage Rating:

100 VAC

Contact Resistance:

50 mΩ max

Cycles:

10,000

RoHS Compliant:

Yes

UUSB

UUSB
= Micro USB 2.0

TYPE

-AB
= Micro AB

-B
= Micro B

PLATING

-F
= Gold Flash on Mating Area and Tails




-S
= 30μ" (0,76 μm) Gold on Mating Area, Gold Flash on Tails

TERMINATION

-SM
= Surface Mount

TR

-TR
= Tape & Reel



-B TYPE

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292
 SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766
 SAMTEC TAIWAN • Tel: 886-2-2735-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683