


REEVITE INDUSTRIAL MOULDINGS LTD
RB1800 GROMMET SEALING RANGE



PART No	METRIC		
	A	B	C
RB 1801	12.5	1.0 - 4.0	3.0 - 5.0
RB 1802	16	1.0 - 4.0	5.0 - 7.0
RB 1803	19	1.0 - 4.0	7.0 - 10.0
RB 1804	23	1.0 - 4.0	10.0 - 14.0
RB1806	25	1.0 - 4.0	10.0 - 15.0
RB 1805	29	1.0 - 4.0	14.0 - 20.0

A = PANEL HOLE
B = PANEL THICKNESS
C = RECOMMENDED CABLE SIZE

Typical Properties of Standard Materials.

Physical Property	TPR
Hardness +/-5 (IRHD)	
Hardness +/-5 (Shore A)	55
Softness +/-5 (BSS)	
Minimum Tensile Strength (Mpa)	5.2
Minimum Elongation at break (%)	400
Maximum Compression set (%) (24 +0/-2 hrs at 70 +/-1 °C)	22
Resistance to accelerated ageing	168 hours at
Change in Hardness (+/-)	3
Maximum reduction in tensile strength (% of original)	2
Maximum reduction in elongation at break (%) of	3
Minimum Continuous Operating Temperature (°C)	-40
Maximum Continuous Operating Temperature (°C)	125
WEEE and RoHS Compliant	YES
Recyclable	YES
Weathering	EXCELLENT

Disclaimer:

The above information is a general guide only for our standard range of stock materials. Testing for the suitability of the material/component for a particular application/environment is the responsibility of the customer.

E&OE

SF 51 - Issue 3. 06/07/2010