



72-9390 SPECIFICATIONS

| Basic Functions | Range | | Best Accuracy |
|--|---|-------------------------------------|---------------|
| | SCAN Mode | AUTO Mode | |
| DC Voltage | 3V/30V/300V | 3V/30V/300V | ±(1%+ 3) |
| AC Voltage | 3V/30V/300V | 3V/30V/300V | ±(1%+ 4) |
| Resistance | 300/3k/30k/300k/3MW 300/3k/30k/300k/3M/30MW | | ± (1%+ 3) |
| Capacitance | 3nF/30nF/300nF/3μF /30μF/300μF | 3nF/30nF/300nF/3 /30μF/300μF/3mF | ± (3%+ 5) |
| Special Functions | | | |
| EF Function | | | |
| Diode | | | ✓ |
| Continuity Buzzer | | | ✓ |
| Sleep Mode | Around 10 Minutes | | ✓ |
| Low Battery Display | | | ✓ |
| Input Impedance for DC Voltage Measurement | ≥ 10MW | | ✓ |
| Data Hold | | | ✓ |
| Max / Min Mode | | | ✓ |
| Display Backlight | | | ✓ |
| Penlight | | | ✓ |
| Max. Display | 3000 | | ✓ |

GENERAL CHARACTERISTICS

| | |
|------------------------------|--|
| Power | 3V Li-MnO2 Button Cell Battery |
| LCD Size | 28 x 14 mm |
| Product Colour | Orange+Grey |
| Product Net Weight | 90g |
| Product Size | 20 x 27 x 182mm |
| Standard Accessories | Test Lead, Battery, English Manual |
| Standard Individual Packing | Blister |
| Standard Quantity Per Carton | 80 pcs |
| Standard Carton Measurement | 570 x 300 x 415mm (0.071 CBM Per Export Carton) |
| Standard Carton Gross Weight | 15kg |

*Available at Extra Cost
Specifications and other information are subject to change without further notice