

**ACT20X**  
**ACT20X-SDI-HDO-L-S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com



The ACT20X-SDI-HDO/2SDI-2HDO valve control modules are controlled from the safe zone on the input side by the switching signals (NPN, PNP) and provide digital outputs to switch actuators (solenoids, alarms) in Ex Zone 0.

Depending on the module, the output current is limited for the ignition protection groups IIC/IIB to 35 mA or 60 mA (only one channel).

Integrated alarm contacts issue an alert in the event of a malfunction; this makes troubleshooting easier and increases the system availability.

The rail mounted disconnect-switch amplifiers are optionally available in one- or two-channel versions. With 11 mm width per channel, the devices need little space in the electrical cabinet.

**General ordering data**

Order No.	<a href="#">8965400000</a>
Type	ACT20X-SDI-HDO-L-S
Version	ACT20X, EX signal isolating converter, 1-channel version, For gas group IIC 35 mA
GTIN (EAN)	4032248785018
Qty.	1 pc(s).

**ACT20X  
ACT20X-SDI-HDO-L-S**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com

**Technical data**

**Dimensions**

Length	119.2 mm	Width	22.5 mm
Height	113.6 mm		

**Temperatures**

Operating temperature	-20 °C...+60 °C	Storage temperature	-20 °C...+85 °C
-----------------------	-----------------	---------------------	-----------------

**input**

Type	NPN, PNP switching signal	Trigger level high	≥ 4.0 V DC (NPN), ≥ 10V DC (PNP)
Triggerlevel low	≤ 2.0 V DC (NPN), ≤ 8.0 V DC (PNP)	Input voltage	≤ 28 V DC
Input resistance, voltage	3.5 kΩ		

**Output**

Residual ripple (current loop)	< 40 mV <sub>eff</sub>
--------------------------------	------------------------

**Alarm output**

Type	Relay, 1 NC (voltage-free)	Nominal switching voltage	≤ 125 V AC / 110 V DC (safe area) ≤ 32 V AC / 32 V DC (Zone 2)
Continuous current	≤ 0.5 A AC / 0.3 A DC (safe zone), ≤ 0.5 A AC / 1 A DC ( Zone 2)	Power rating	≤ 62.5 VA / 32 W (safe area) ≤ 16 VA / 32 W (Zone 2)

**General specifications**

Supply voltage	19.2 – 31.2 V DC	Type of connection	Screw connection
Power consumption	≤ 3 W (2 channels)	Protection degree	IP 20
Humidity	0...95 % (no condensation)		

**Insulation coordination**

EMC standards	DIN EN 61326	Insulation voltage	2.6 kV (input / output)
Rated voltage	300 V		

**Data for Ex applications (ATEX)**

Voltage U <sub>0</sub>	28 V DC	Current I <sub>0</sub>	≤ 110 mA
Power P <sub>0</sub>	≤ 0.77 W		

**Ratings IECEx/ATEX**

Certificate No. (ATEX)	KEMA10ATEX0019X	Certificate No. (IECEx)	IECExKEM09.0071X
------------------------	-----------------	-------------------------	------------------

**Classifications**

ETIM 3.0	EC002479	ETIM 4.0	EC002479
UNSPSC	30-21-18-01	eClass 5.1	27-21-01-07
eClass 6.0	27-21-01-07		

**Datasheet**

**ACT20X**  
**ACT20X-SDI-HDO-L-S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**

**Approvals**

---

Approvals	CULUS; FMEX; IECEXKEM; KEMAATEX
-----------	------------------------------------


---

**ACT20X  
ACT20X-SDI-HDO-L-S**


**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com


**Drawings**


**Electric symbol**



**Circuit diagram**



 Zone 0, 1, 2, 20, 21, 22 /  
Cl. I/II/III, div. 1 gr. A-G

 Zone 2 / Cl. 1, div. 2,  
gr. A-D or safe area