Product data sheet Characteristics

XB4RFB01

Pack SPS - XB4 - Ø22 mm metal - non progammable receiver - 24 V DC



Main Range of product Harmony XB4R Product or component Wireless and batteryless package type XB4R Device short name Head material Metal Kit composition 1 metal pushbutton, 1 receiver and 1 set of caps

Complementary


Control type	Wireless and batteryless pushbutton Ø 22 mm assembled on fixing collar				
Type of receiver	Non-programmable receiver (1 relay)				
[Us] rated supply voltage	24 V DC				
Catalog part number	ZBRT1 ZBA79 Paired receiver ZB4RZA0 ZB4BZ009				
Environment					
Product certifications	CSA				

ļ	n	V	ır	0	n	ır	n	е	n	ι

Product certifications	CSA	
1 Toddet certifications		
	C-Tick	
	GOST	
	UL	
	ANATEL	
	SRRC	
	SKKU	
Marking	CE	
Standards	IEC 6100-4-2	
	IEC 6100-4-3	
	IEC 6100-4-4	
	IEC 6100-4-5	
	IEC 6100-4-6	
	IEC 6100-4-11	
	IEC 0100-4-11	


XB4RFB01

Non-Programmable Receiver



Wireless and Batteryless Pushbutton - Transmitter

With Metal Pushbutton and Cap




e: panel thickness 1 to 6 mm / 0.039 to 0.24 in.

Product data sheet Mounting and Clearance


XB4RFB01

Receiver Clearance



- (1) Drive(2) Power Supply or PLC

Receiver Mounting




Product data sheet Connections and Schema

XB4RFB01

Non-Programmable Receiver

Wiring Diagram



- (1) 125 mA fas (2) Imax = 3 A 125 mA fast-blow fuse