

Spezifikation für Freigabe / specification for release

Kunde / customer : _____
 Artikelnummer / part number : **74271131S**
 Bezeichnung : **STAR-TEC mit Sicherheitsverschluss**
 description : **STAR-TEC with Safety Lock**



DATUM / DATE : 2008-01-03

A Mechanische Abmessungen / dimensions:

| | | | | |
|---|------------------|------------------|------------------|---|
| | | | | |
| a | b | c | c | |
| a | b | c | c | |
| | | | | für Kabeldurchmesser / for cable diameter |
| | | | | Ø |
| | 24,5 typ. | 40,5 typ. | 21,0 typ. | 6 - 7,5 |
| | mm | mm | mm | mm |

B Elektrische Eigenschaften / electrical properties:

| Eigenschaften / properties | Testbedingungen / test conditions | | Wert / value | Einheit / unit | Tol. |
|--------------------------------------|-----------------------------------|---|--------------|----------------|-------|
| Impedanz @ 1 Wg./ impedance @ 1 turn | 25 MHz | Z | 145 | Ω | ± 25% |
| Impedanz @ 1 Wg./ impedance @ 1 turn | 100 MHz | Z | 246 | Ω | ± 25% |
| Impedanz @ 2 Wg./ impedance @ 2 turn | 25 MHz | Z | 607 | Ω | typ. |
| Impedanz @ 2 Wg./ impedance @ 2 turn | 100 MHz | Z | 755 | Ω | typ. |

C



D Prüfgeräte / test equipment:

HP 4191 B für/for Z und/and material
16092A - Klemme / clamp
AWG26 - Ø 0,5mm - Länge/length: 165 mm

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%
 Umgebungstemperatur / temperature: + 20°C

F Werkstoffe & Zulassungen / material & approvals:

Basismaterial / base material: 4 W 620
 Kunststoff / plastic material: PA 66 / 6
 UL-Zulassungen / UL-approval: UL94-V0 / E53898
 Farbe / colour: schwarz / black

G Eigenschaften / general specifications:

Curietemperatur / curie temperature: + 150°C
 Gewicht / weight: 34,0g typ.
 Lagertemperatur / storage temperature: -40°C ~ + 85°C
 Betriebstemp. / operating temperature: -25°C ~ +105°C

| | | | |
|-------------------------------------|--------------------------|------|--------------------------------------|
| Freigabe erteilt / general release: | Kunde / customer | | |
| | | SMU | Version 6 08-01-03 |
| Datum / date | Unterschrift / signature | SMU | Version 5 07-01-22 |
| | Würth Elektronik | AF | Version 4 06-11-13 |
| | | SMU | Version 3 06-11-13 |
| Geprüft / checked | Kontrolliert / approved | LF | Version 2 04-10-11 |
| | | JH | Version 1 00-12-06 |
| | | Name | Änderung / modification Datum / date |

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>


Spezifikation für Freigabe / specification for release

Kunde / customer : _____
 Artikelnummer / part number : **74271131S**
 Bezeichnung : **STAR-TEC mit Sicherheitsverschluss**
 description : **STAR-TEC with Safety Lock**



DATUM / DATE : 2008-01-03

H Impedanzverlauf / impedance curve:



A: 2 x durch Bohrung Ferrit / 2 x times through ferrite

B: 1 x durch Bohrung Ferrit / 1 x times through ferrite

| | | | | |
|-------------------------------------|--------------------------|------|-------------------------|--------------|
| Freigabe erteilt / general release: | Kunde / customer | | | |
| | | | | |
| Datum / date | Unterschrift / signature | | | |
| | | | | |
| | Würth Elektronik | | | |
| | | | | |
| Geprüft / checked | Kontrolliert / approved | Name | Änderung / modification | Datum / date |
| | | | | |

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400

<http://www.we-online.com>