

Technibond Limited

THE VALLEY CENTRE HIGH WYCOMBE BUCKS HP13 6EQ ENGLAND
Telephone High Wycombe (0494) 448791 Fax 465110 Telex 838727

Company Registration No 1593212, England VAT Registration No 349 1208 59
Registered Office 55 Station Road Beaconsfield Bucks HP9 1QL

TECHNIBOND T526 Lightweight Filmic Double-Sided Tape

CONSTRUCTION

Adhesive: Permanent high tack rubber based adhesive.

Carrier: Thin clear polyester film.

Liner: White kraft release paper.

PROPERTIES

Thickness	carrier + adhesive	:	0.075mm
	liner	:	0.075mm
Peel adhesion (20 mins)	open side	:	400 N/m
	closed side	:	400 N/m
Peel adhesion (24 hrs)	open side	:	500 N/m
	closed side	:	500 N/m
Shear (1 kg)	open side	:	1 hour
	closed side	:	1 hour
Temperature range		:	-20°C to +100°C

APPLICATIONS

Technibond T526 is used for lightweight and general purpose fixing, and for holding components during assembly. It is suitable for a variety of smooth, flexible materials such as paper, thin cards and foils, and plastic films. The high adhesive tack gives an almost immediate bond, and the polypropylene film gives the product good strength and dimensional stability.

SHELF LIFE

One year when stored in original packaging in a cool, dry place.

Technibond offer these materials in good faith and certify that they are produced to the highest possible production standards.

No liability can be held against the company for products incorrectly used or failure incurred. We therefore, strongly recommend that samples of the intended product are tested for complete compatibility with the proposed application before order commitments are entered into.

APRIL 89