


BU508A, 508D

Horizontal Deflection Transistors




High Voltage Switching



Specifically designed for use in large screen colour deflection circuits.

Features:

- Collector-Emitter Sustaining Voltage -
 $V_{CEX} = 1500V$ (Minimum) - BU508A, BU508D.
- Glassivated Base-Collector Junction.



- Pin 1. Base
2. Collector
3. Emitter

Dimensions	Minimum	Maximum
A	20.63	22.38
B	15.38	16.20
C	1.90	2.70
D	5.10	6.10
E	14.81	15.22
F	11.72	12.84
G	4.20	4.50
H	1.82	2.46
I	2.92	3.23
J	0.89	1.53
K	5.26	5.66
L	18.50	21.50
M	4.68	5.36
N	2.40	2.80
O	3.25	3.65
P	0.55	0.70

Dimensions : Millimetres

NPN
BU508A
BU508D

5 Ampere
Power
Transistors
1500 Volts
125 Watts



TO-247(3P)

BU508A, 508D

Horizontal Deflection Transistors




Maximum Ratings

Characteristic	Symbol	Rating	Unit
Collector-Emitter Voltage	V_{CEO}	700	V
Collector-Emitter Voltage ($V_{BE} = 0$)	V_{CES}	1500	
Emitter-Base Voltage	V_{EBO}	5.0	
Collector Current-Continuous -Peak	I_C	5.0 8.0	A
Base Current-Continuous	I_B	2.5	
Total Power Dissipation at $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	125 1.0	W W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-65 to +150	$^\circ\text{C}$

Thermal Characteristics

Characteristic	Symbol	Maximum	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	1.0	$^\circ\text{C}/\text{W}$

Figure - 1 Power Derating



BU508A, 508D

Horizontal Deflection Transistors



Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Minimum	Maximum	Unit	
OFF Characteristics					
Collector-Emitter Sustaining Voltage (1) ($I_C = 100\text{mA}$, $I_B = 0$)	$V_{CE(sus)}$	700	-	V	
Collector Cut off Current ($V_{CE} = 1500\text{V}$, $V_{BE} = 0$)	I_{CES}	-	1.0	mA	
Emitter Cut off Current ($V_{EB} = 5.0\text{V}$, $I_C = 0$) BU508A BU508D	I_{EBO}	-	10 300		
ON Characteristics (1)					
Collector-Emitter Saturation Voltage ($I_C = 4.5\text{A}$, $I_B = 2.0\text{A}$) BU508A, BU508D	$V_{CE(sat)}$	-	1.0	V	
Base-Emitter Saturation Voltage ($I_C = 4.5\text{A}$, $I_B = 2.0\text{A}$)	$V_{BE(sat)}$	-	1.5		
Diode Forward Voltage ($I_F = 4.0\text{A}$) BU508D	V_F	-	2.0		
Dynamic Characteristics					
Current Gain-Bandwidth Product ($I_C = 0.1\text{A}$, $V_{CE} = 5.0\text{V}$, $f = 1.0\text{MHz}$)	f_T	4.0 (Typical)	-	MHz	
Output Capacitance ($V_{CE} = 10\text{V}$, $I_E = 0$, $f = 1.0\text{MHz}$)	C_{ob}	125 (Typical)	-	pF	
Switching Characteristics					
Storage Time	$I_C = 4.5\text{A}$, $I_{B1} = 1.4\text{A}$, $L_B = 10\mu\text{H}$	t_s	7.0 (Typical)	-	μs
Fall Time		t_f	1.0 (Typical)	-	






(1) Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2.0\%$

BU508A, 508D

Horizontal Deflection Transistors



BU508A







BU508A, 508D

Horizontal Deflection Transistors



BU508D



Specifications

$I_{C(av)}$ maximum (A)	V_{CEO} maximum (V)	V_{CES} maximum (V)	$V_{CE(Sat)}$ (V) at $I_C = 4.5\text{A}$	P_{tot} at 25°C (W)	Package	Type	Part Number
5	700	1500	1	125	TO-247	NPN	BU508A
							BU508D



BU508A, 508D

Horizontal Deflection Transistors



Notes:

International Sales Offices:



AUSTRALIA – Farnell InOne
Tel No: ++ 61 2 9645 8888
Fax No: ++ 61 2 9644 7898



FINLAND – Farnell InOne
Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411



NETHERLANDS – Farnell InOne
Tel No: ++ 31 30 241 7373
Fax No: ++ 31 30 241 7333



SWITZERLAND – Farnell InOne
Tel No: ++ 41 1 204 64 64
Fax No: ++ 41 1 204 64 54



AUSTRIA – Farnell InOne
Tel No: ++ 43 662 2180 680
Fax No: ++ 43 662 2180 670



FRANCE – Farnell InOne
Tel No: ++ 33 474 68 99 99
Fax No: ++ 33 474 68 99 90



NEW ZEALAND – Farnell InOne
Tel No: ++ 64 9 357 0646
Fax No: ++ 64 9 357 0656



UK – Farnell InOne
Tel No: ++ 44 8701 200 200
Fax No: ++ 44 8701 200 201



BELGIUM – Farnell InOne
Tel No: ++ 32 3 475 2810
Fax No: ++ 32 3 227 3648



GERMANY – Farnell InOne
Tel No: ++ 49 89 61 39 39 39
Fax No: ++ 49 89 613 59 01



NORWAY – Farnell InOne
Tel No: ++ 45 44 53 66 66
Fax No: ++ 45 44 53 66 02



UK – BuckHickman InOne
++ 44 8450 510 150
++ 44 8450 510 130



BRAZIL – Farnell-Newark InOne
Tel No: ++ 55 11 4066 9400
Fax No: ++ 55 11 4066 9410



HONG KONG – Farnell-Newark InOne
Tel No: ++ 852 2268 9888
Fax No: ++ 852 2268 9899



PORTUGAL – Farnell InOne
Tel No: ++ 34 93 475 8804
Fax No: ++ 34 93 474 5288



UK – CPC
++ 44 8701 202 530
++ 44 8701 202 531



CHINA – Farnell-Newark InOne
Tel No: ++86 10 6238 5152
Fax No: ++86 10 6238 5022



IRELAND – Farnell InOne
Tel No: ++ 353 1 830 9277
Fax No: ++ 353 1 830 9016



SINGAPORE – Farnell-Newark InOne
Tel No: ++ 65 6788 0200
Fax No: ++ 65 6788 0300



EXPORT – Farnell InOne
Tel No: ++ 44 8701 200 208
Fax No: ++ 44 8701 200 209

For enquiries from all other markets



DENMARK – Farnell InOne
Tel No: ++ 45 44 53 66 44
Fax No: ++ 45 44 53 66 06



ITALY – Farnell InOne
Tel No: ++ 39 02 93 995 200
Fax No: ++ 39 02 93 995 300



SPAIN – Farnell InOne
Tel No: ++ 34 93 475 8805
Fax No: ++ 34 93 474 5107



ESTONIA – Farnell InOne
Tel No: ++ 358 9 560 7780
Fax No: ++ 358 9 345 5411



MALAYSIA – Farnell-Newark InOne
Tel No: ++ 60 3 7873 8000
Fax No: ++ 60 3 7873 7000



SWEDEN – Farnell InOne
Tel No: ++ 46 8 730 50 00
Fax No: ++ 46 8 83 52 62

<http://www.farnellinone.com>

<http://www.buckhickmaninone.com>

<http://www.cpc.co.uk>

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2004.

