



## Main

Range of product	Harmony 9001K
Product or component type	Pilot light
Component name	9001K
Bezel material	Chromium plated metal
Mounting diameter	30 mm
Shape of signaling unit head	Octagonal
Light source	Bulb included
Bulb base	BA 9s
Bulb type	High luminosity LED
Cap/Operator or lens colour	White
[Us] rated supply voltage	24 V AC/DC
Light block supply	Direct
Connections - terminals	Screw clamp terminals , 1 x 0.22...2 x 1.5 mm <sup>2</sup> conforming to IEC 60947-1

## Complementary

Tightening torque	0.8 N.m cross slotted screw head conforming to IEC 60947-1
Operating position	Any position
[Ui] rated insulation voltage	250 V pollution degree 2 conforming to IEC 60947-1
[Uimp] rated impulse withstand voltage	2.5 kV conforming to IEC 60947-1
Short circuit protection	10 A cartridge fuse protection conforming to IEC 60947-5-1
[Ith] conventional free air thermal current	10 A
Product weight	0.134 kg

## Environment

Standards	CSA C22-2 No 14 EN/IEC 60947-5-1 IEC 60947-1 IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Vibration resistance	7 gn (f = 2...500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn conforming to IEC 60068-2-27
Class of protection against electric shock	Class II conforming to IEC 60536
IP degree of protection	IP66 conforming to IEC 60529 IP66 conforming to NF C 20-010
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 NEMA 6

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

---

RoHS EUR status	Will be compliant
RoHS EUR conformity date	2Q2009

---