tyco Electronics

SAFETY DATA SHEET

Based on Directive 2001/58/EC of the Commission of the European Communities

THERMOFIT HEAT-SHRINKABLE POLYMERIC PRODUCTS

Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation:

Synonyms: Tubing: AP-2000, APTR, AST, AST-FR, AT099, ATUM, BLOX-100, CAPT, C-BLOCK, CBS, CGAT, CGPT, CGTM, CGVT, CPVC, CRN, DCPT, DWP, DWTC, FOIT, FOPT, FTB, FTS, GPO-135, GPT, GPT-FR, GSTB, HCDR, HFR-FR, HSR-HF, HSR-FR, HTAT, HT-SCE, LSTT, LTMS, NT, RAYBLOCK, RAYRIM, RBK-ESS, RBK-GTR, RBK-ILS-85, RBK-ILS-125, RBK-MTS, RBK-VWS, RNF-100, RNF-3000, RP-4800, RPPM, RPS, RT-3, RT-15, RT-102, RT-876, SCL, SRFR, TAT-125, TMS, TMS-SCE, TPEM, TRSA, TUGA, TW-TMS, UWCS, VERSAFIT, WMTM, WNTM, ZHS

Moulded Parts Type: -3, -4, -6, -8, -15, -25, -130, PD CAPS, TC-400X

: N.A. : N.A. : RAY/3122E Revision 5 Reference CAS no.

EC index No. EINECS No. : N.D. NFPA code Molecular weight : N.A. : N.A. RTECS No. Formula

1.2 Use of the substance or the preparation:

Heat-Shrinkable Polymeric Products

Company/undertaking identification:

TYCO Electronics

Cheney Manor Industrial Estate SN2 2QE Swindon, United Kingdom Tel.: +44 1793 57 38 24 Fax: +44 1793 57 39 53

1.4 Telephone number for emergency: +32 14 58 45 45

Brandweerinformatiecentrum voor gevaarlijke stoffen (B.I.G.) Technische Schoolstraat 43A, B-2440 Geel

Composition/information on ingredients

Plastic materials may be based on polyethylene and olefin copolymers, chloropolymers, polyamides or silicones. Products may be coated with, or used in conjunction with adhesives/mastics based on polyamides and/or olefin copolymer

For products coated with Tyco Electronics Unicure-225 precatalysed epoxy resin adhesive, refer to supplementary information on Tyco Electronics SDS RAY/3111E

Hazards identification 3.

- This Safety Data Sheet applies to a group of products which are not hazardous as supplied in accordance with EC-directives 67/548/EEC and 1999/45/EEC
- Products may emit hazardous thermal decomposition products if overheated or burnt (see section 10.3)

First aid measures

4.1 Eye contact:

If molten material contacts the eye: Rinse immediately with plenty of water for 15 minutes Consult a doctor/medical service if irritation persists

Printing date 06-2002

Compiled by Brandweerinformatiecentrum voor Gevaarlijke Stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

2 +32 14 58 45 47 http://www.big.be E-mail: info@big.be

: 27-03-2002 : 005 MSDS established Revision date Revision number Reference number : BIG\24601GB

Reason for revision : Directive 2001/58/EC

- 4.2 Skin contact:
 If molten material contacts the skin:
 immediately flush with cold water for 15 minutes
 do not attempt to remove material stuck to the skin treat as a burn
 - Consult a doctor/medical service

4.3 After inhalation:

- If exposed to fumes from overheated or burnt material: remove the victim into fresh air
- keep warm and at rest Consult a doctor/medical service if breathing problems develop

4.4 After ingestion: - Not applicable

Fire-fighting measures

5.1 Suitable extinguishing media:

- Water spray
- Polyvalent foam ABC powder
- Carbon dioxide

5.2 Unsuitable extinguishing media:

- No data available

5.4 Instructions:

Not applicable

5.5 Special protective equipment for firefighters:

- Self-contained breathing apparatus with full face piece Protective clothing for exposure to chemicals

Accidental release measures

- **6.1** Personal protection/precautions: see heading 8.1/8.3/10.3

6.3 Clean-up:

Pick up for continued use or disposal

Handling and storage

7.1 Handling:

- Refer to Tyco Electronics product installation instructions
- Avoid overheating the product after shrinkage has occurredStop heating immediately if the product blisters, chars or shows other signs
- of degradation Avoid inhaling fumes which may be released and ventilate the area thoroughly before resuming work

- Avoid contact with molten material
 Wash hands before eating, drinking or smoking
 Practice good standards of personal and industrial hygiene

Printing date : 06-2002 2 / 7

7.2 Storage:

- Store in a dry area Store in a cool area
- Product should be stored at temperatures below 40°C to avoid prerecovery of expanded product
- Store in the original packaging
- Keep away from: heat sources

Storage temperature **:** < 40 ٥C Quantity limits Storage life : N.D. kg : N.D.

Materials for packaging

- suitable : no data available

- to avoid : no data available

7.3 Specific uses:

- See information supplied by the manufacturer

Exposure controls/Personal protection

8.1 Exposure limit values:

- Not applicable

Sampling methods:

- No data available

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Work under local exhaust/ventilation
- When using gas torches in confined spaces ensure an adequate supply of fresh air to avoid oxygen depletion

8.2.2 Environmental exposure controls: see heading 13

8.3 Personal protection:

- 8.3.1 respiratory protection:

 Not required for normal conditions of use
 Approved respirator or self contained breathing apparatus for installations in confined/unventilated areas

8.3.2 hand protection:

- Heat resistant gloves if handling hot products after installation Suitable materials: No data available
- Breakthrough time: N.D.

8.3.3 eye protection:

Safety glasses with side shield, goggles or face shield depending on application

8.3.4 skin protection:

- Protective clothing Suitable materials:

No data available

Printing date : 06-2002 3 / 7

9. Physical and chemical properties

9.1 General information:

Appearance (at 20°C) : Plastic tubing and moulded parts

Odour : Almost odourless
Colour : Variable in colour

9.2 Important health, safety and environmental information:

```
pH value
                                              : N.D.
                                                              ٥C
Boiling point/boiling range
                                             : N.D.
Flashpoint
                                                              ٥C
                                             : N.D.
                                             : N.D. : N.D.
                                                              vol% (
                                                                        °C)
Explosion limits
Vapour pressure (at 20°C)
Vapour pressure (at 50°C)
                                                              hPa
                                             : N.D.
                                                             hPa
                                               0.9/2.2
Relative density (at 20°C)
Water solubility
                                             : Insoluble
Soluble in
                                             : N.D.
                                             : N.D.
Relative vapour density
Viscosity
                                             : N.D.
                                                             Pa.s
Partition coëfficient n-octanol/water
                                             : N.D.
Evaporation rate
  ratio to butyl acetate ratio to ether
                                              : N.D.
                                             : N.D.
```

9.3 Other information:

Melting point/melting range : 70/170 °C (Adhesives) Auto-ignition point : N.D. °C Saturation concentration : N.D. g/m^3

10. Stability and reactivity

10.1 Conditions to avoid/reactivity:

- Stable under normal conditions

10.2 Materials to avoid:

- Keep away from: heat sources

10.3 Hazardous decomposition products:

- Thermal decomposition is not significant when products are used in accordance with Tyco Electronics product installation instructions
- At higher temperatures and if materials burn, thermal decomposition products will depend on the base polymer used and may include, but are not limited to : alcohols, aldehydes, carbon monoxide, carbon dioxide, hydrocarbons, hydrogen bromide, hydrogen chloride, silicon dioxide and oxides of nitrogen, phosphorus and sulphur

11. Toxicological information

11.1 Acute toxicity:

LD50 oral rat LD50 dermal rat LD50 dermal rabbit	:	N.D. N.D. N.D.	mg/kg mg/kg mg/kg
LC50 inhalation rat		N.D.	mg/kg $mg/1/4 h$
LC50 inhalation rat	:	N.D.	ppm/4 h

Printing date : 06-2002 4 / 7

11.2 Chronic toxicity:

EC carc. cat. : not listed not listed
not listed EC muta. cat. EC repr. cat. Carcinogenicity (TLV) : not listed IARC classification : not listed

11.3 Routes of exposure: inhalation of thermal decomposition products

11.4 Acute effects/symptoms:

- AFTER INHALATION
- Overheating products during installation may produce vapours/fumes that can cause irritation of the respiratory tract

 Symptoms may include coughing, headache, dizziness, nausea and in the absence of ventilation, possible asphyxiation
- AFTER SKIN CONTACTContact with molten material may cause thermal burns
- AFTER EYE CONTACT
- Overheating products during installation may produce vapours/fumes that can cause irritation and redness of the eye tissue
- AFTER INGESTIONNot a normal route of exposure

11.5 Chronic effects:

- None known

12. **Ecological information**

12.1 Ecotoxicity:

- No data available

12.2 Mobility:

- Volatile organic compounds (VOC): N.D.%
- Insoluble in water

For other physicochemical properties see heading 9.

12.3 Persistence and degradability:

% ThOD - biodegradation BOD₅ N.D.

- water - Not readily biodegradable in water

- test: OECD

: T ½: N.D. - soil days

12.4 Bioaccumulative potential:

- log P_{ow} : N.D. : N.D.

12.5 Other adverse effects:

: N.D. - WCK

 Effect on the ozone layer : Not dangerous for the ozone layer

(1999/45/EC)

: no data available : no data available - Greenhouse effect - Effect on waste water purification

Printing date : 06-2002 5 / 7

Disposal considerations

13.1 Provisions relating to waste:
 - Waste material code (75/442/EEC, Council Decision 2001/118/EC, O.J. L47 of
 16/2/2001): 07 02 13 (waste plastic)
 - Waste material code (Flanders): 551, 567

13.2 Disposal methods:
 - Landfill or incinerate at an approved site in accordance with national and

- Landilli of Incinerate at an approved bits in describing local regulations
- Recycle/reuse
- Remove to an authorized dump (Class II)
- For incineration use a high temperature incinerator equipped with secondary combustion chamber and acid gas scrubber
- Do not discharge to wastewater treatment installation

13.3 Packaging/Container: - No available data

Transport information

14.1	Classification of the substance in compliance UN number CLASS SUB RISKS PACKING PROPER SHIPPING NAME	€ V :	with	UN Recommendations
14.2	ADR (transport by road) CLASS PACKING or CLASSIFICATION CODE DANGER LABEL TANKS DANGER LABEL PACKAGES	:	NOT	SUBJECT
14.3	RID (transport by rail) CLASS PACKING OR CLASSIFICATION CODE DANGER LABEL TANKS DANGER LABEL PACKAGES	:		
14.4	ADNR (transport by inland waterways) CLASS PACKING OR CLASSIFICATION CODE DANGER LABEL TANKS DANGER LABEL PACKAGES	:	NOT	SUBJECT
14.5	IMDG (maritime transport) CLASS SUB RISKS PACKING MFAG EMS MARINE POLLUTANT	:	NOT	SUBJECT
14.6	ICAO (air transport) CLASS SUB RISKS PACKING PACKING PACKING INSTRUCTIONS PASSENGER AIRCRAFT PACKING INSTRUCTIONS CARGO AIRCRAFT	:	NOT	SUBJECT
14.7	Special precautions in connection with transport	:		restricted for any mode of ernational transport
14.8	Limited quantities (LQ)	:		

6 / 7 Printing date : 06-2002

Regulatory information

Classification according to directives 67/548/EEC and 1999/45/EC (**: see heading 16)

NOT APPLICABLE

16. Other information

Users are advised that they may have additional disclosure obligations under other national and local laws. Users are advised to ensure that this information is brought to the attention of all employees, agents, and contractors handling this product. Users of Tyco Electronics products should make their own evaluation to determine the suitability of each such product for the specific application and to establish safe handling and installation procedures. Distributors of this product are advised to forward this document, or the information contained herein, to every purchaser of this product.

Tyco Electronics makes no warranties as to the accuracy or completeness of this information and disclaims any liability in connection with its use. Tyco Electronics obligations shall be only as set forth in Tyco Electronics standard terms and conditions of sale for this product. In no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of this product.

NOT APPLICABLE N.A. = = NOT DETERMINED N.D.

INTERNAL CLASSIFICATION

(**) Labelling:

The labelling of the substance described in this MSDS complies with the provisions of Directive 1999/45/EC of 31 May 2001, published in the Official Journal of the European Communities L 200 of 30/07/1999. This Directive replaces Directive 88/379/EEC of 7 June 1988, published in the Official Journal of the European Communities L 187 of 16/07/1988. Member States shall apply the laws, regulations and administrative provisions referred to in article 22 of this Directive:

- (a) to preparations not within the scope of Directive 91/414/EEC or Directive 98/8/EC as from 30 July 2002; and
- (b) to preparations within the scope of Directive 91/414/EEC or Directive 98/8/EC as from 30 July 2004.

Exposure limits:

TLV Threshold Limit Value - ACGIH USA 2000

ORS Occupational Exposure Standards - United Kingdom 1999

MET. Maximum Exposure Limits - United Kingdom 1999

MAK Maximale Arbeitsplatzkonzentrationen - Germany 2001

TRK

Technische Richtkonzentrationen - Germany 2001 Maximale aanvaarde concentratie - The Netherlands 2002 Valeurs limites de Moyenne d'Exposition - France 1999 MAC VME Valeurs limites d'Exposition à court terme - France 1999 VLE Grenswaarde beroepsmatige blootstelling - Belgium 1998 Grenswaarde kortstondige blootstelling - Belgium 1998 GWBB

GWK Indicative occupational exposure limit values - directive 2000/39/EC EC

Printing date : 06-2002 7 / 7