Temperature Controlled Soldering Station



Features:

- The ZD-937 soldering station is an ideal soldering tool for hobbyist or occasional use.
- It has the function of regulating temperature, 1°C or 10°C per grade can be regulated using the control buttons.
- Preset buttons of 200, 300 and 400 are also included.
- The station can be switched between °C and °F.
- Contents of station: power unit, soldering iron (with a conical tip), user instructions.

Specifications:

Power supply voltage

Electric iron power Equipment power supply fuse Regulating scope of temperature Temperature display

Display precision Circumstance humidity

Atmospheric pressure Shell size (W x H x D) Weight 230 volt (220 to 240 Volt)/50Hz.
: 48 watt.
: T1 A/250 volt (50 x 20mm glass pipe).
: 150° to 450°C.
: 2 x 31/2 grades LCD display. Display scope : 150° to 450°C.
: 5%.
: +5°C to +40°C. Relative humidity : <85% (not in humidification).
: 600 to 1000HPa.
: 210 x 125 x 135mm (without electric iron).
: About 1800 grams.

: 110 volt (110 to 130 volt)/60Hz

Specification Table

Description	Voltage Supply (V)	Part Number
Soldering Station, UK Plug	110 to 130	D00675
Soldering Station, EU Plug	220 to 240	D00676

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheets hould check for themselves the Information on use of it (including liability for its accuracy or where the Group was aware of the possibility of such loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2009.



http://www.farnell.com http://www.newark.com http://www.cpc.co.uk