

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 5

NC-AA NO CLEAN WICK

SDS no. : 249903 V001.3 Revision: 13.02.2009 printing date: 14.05.2009

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

NC-AA NO CLEAN WICK

Intended use:

Desoldering wick

Company name:

Henkel AG & Co. KGaA Henkelstr. 67 40191 Düsseldorf

Germany

Phone: +49 (211) 797-0

E-mail address of person responsible for Safety Data Sheet:

ua-productsafety.uk@uk.henkel.com

Emergency information:

24 Hours Emergency Tel: +44 (0)20 8312 0291

2. Hazards identification

This product contains modified rosin. Fumes evolved at soldering temperatures will irritate the nose, throat and lungs.

3. Composition / information on ingredients

Declaration of ingredients according to (EC) No 1907/2006:

Hazardous components CAS-No.	EINECS ELINCS	content	Classification
Copper Metal 7440-50-8	231-159-6	80 - 100 %	No classification required.

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Eye contact:

Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical attention.

Ingestion:

Do not induce vomiting.

Seek medical advice.

5. Fire fighting measures

Combustion behaviour:

The product itself does not burn. Any fire extinguishing action should be appropriate to the surroundings.

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

Do not use water on fires where molten metal is present.

Special protection equipment for firefighters:

Wear self-contained breathing apparatus. Wear protective equipment.

Hazardous combustion products:

High temperatures may produce heavy metal dust, fumes or vapours., Thermal decomposition can lead to release of irritating gases and vapors.

6. Accidental release measures

Personal precautions:

Avoid contact with skin and eyes.

Environmental precautions:

Do not empty into drains / surface water / ground water.

Clean-up methods:

Scrape up spilled material and place in a closed container for disposal.

7. Handling and storage

Handling:

Extraction is necessary to remove fumes evolved during reflow. When using do not eat, drink or smoke.

Wash hands before breaks and immediately after handling the product.

Storage:

Store in a cool, dry place.

8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Valid for Great Britain Basis

UK EH40 WELs

Ingredient	ppm	mg/m3	Туре	Category	Remarks
COPPER, INHALABLE DUSTS AND		2	Short Term Exposure		EH40 WEL
MISTS (AS CU)			Limit (STEL):		
7440-50-8					
COPPER, FUME		0,2	Time Weighted Average		EH40 WEL
7440-50-8			(TWA).		
COPPER, INHALABLE DUSTS AND		1	Time Weighted Average		EH40 WEL
MISTS (AS CU)			(TWA).		
7440-50-8					
COPPER, FUME				Listed.	EH40 WEL
7440-50-8					
COPPER, INHALABLE DUSTS AND				Listed.	EH40 WEL
MISTS (AS CU)					
7440-50-8					

Engineering controls:

Extraction is necessary to remove fumes evolved during reflow.

Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

9. Physical and chemical properties

solid

copper

None

General characteristics	
Appearance	

Odor:

Phys./chem. properties:

pH-value Boiling point Density 0 Solubility (qualitative) Melting point Octanol/Water distribution coefficient not applicable Not determined 8,9000 g/cm3

Insoluble 1.083,0 °C (1981.4 °F) Not determined

10. Stability and reactivity

Conditions to avoid:

Stable under recommended storage conditions.

Materials to avoid:

Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

Hazardous decomposition products:

Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological information

Oral toxicity:

This material is considered to have low toxicity if swallowed.

Inhalative toxicity:

Fumes evolved at soldering temperatures will irritate the nose, throat and lungs. Prolonged or repeated exposure to flux fumes may result in sensitisation in sensitive workers.

Dermal toxicity:

This product is considered to have low dermal toxicity.

Skin irritation:

Fumes emitted during soldering may irritate the skin.

Eye irritation:

Fumes emitted during soldering may irritate the eyes.

12. Ecological information

Mobility:

The product is insoluble and sinks in water.

Persistence and Biodegradability:

The product is not biodegradable.

Bioaccumulative potential:

Octanol/Water distribution coefficient: Not determined

General ecological information:

Do not empty into drains / surface water / ground water.

13. Disposal considerations

Product disposal:

Wherever possible unwanted solder alloy should be recycled for recovery of metal. Otherwise dispose of in accordance with local and national regulations.

Waste code(EWC):

06 04 05 - wastes containing other heavy metals

Disposal of uncleaned packages:

Dispose of as unused product.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. Regulations - classification and identification

Indication of danger:

none

Risk phrases:

Not classified as hazardous.

Safety phrases:

not applicable

Additional information:

Avoid breathing fumes given out during soldering.

National regulations/information (Great Britain):

RemarksThe Health & Safety at Work Act 1974.The Control of Substances Hazardous to Health Regulations. L5:General Approved Code of Practice to the COSHH Regulations. HS(G)97:A Step by S Guide to the COSHH Regulations. HS(G)193:COSHH essentials: Easy steps t control chemicals.IND (G)248L:Solder fume and you. IND(G)249L:Controlling health risks fro rosin (colophony) based solder fluxes.	0

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.