# **ZARGES K470 Universal Aluminium Container**

The ZARGES K470 universal container offers a professional, secure and lightweight solution

for transporting valuable equipment and tools.

Tested by independent institutes around the world, the K470 is rugged, lockable and water resistant\* so whatever you need to carry and protect and wherever it's going the K470 aluminium container is ready for the task.





#### **SPECIFICATION:**

RS	Manufacturers	Inside Dimensions	Outside Dimensions	Volume	Weight
Stock	Part No.	LxWxH	LxWxH	(L)	(Kg)
No.		Approx. mm	Approx. mm		
290-2784	40565	750 x 550 x 380	800 x 600 x 410	157	10

### **FEATURES:**

- → Solid, but lightweight aluminium panels, lid and base give you the professional look and ensure years of service
- Optimum comfort and durability with oversized handles and latches
- \*Protection against splash water and dust ingress, IP54 rated
- Aluminium stacking corners for extra rigidity and safe stacking
- Profile-section joints fully welded
- Stainless steel hinge strip, riveted into lid and panels
- Extra strong 1.5 mm sheet with all K470 from 750 x 550mm base dimension
- Lockable catches (max. shackle thickness 6 mm)

#### **NOTES:**

Version with protection against water jets to class IP 65 available as an option UN approval for the transportation of hazardous goods possible at additional charge Special foam inserts available on request



## Precision engineering. It's all in the detail of the K470

Superiority starts with the little things. Top quality is always a question of detail. And that's precisely why we've made our universal containers not just the market leader but the leader in terms of quality too!



All-round foamed lid seal

Preventative protection against wear, overloading and squashing



Stainless steel hinges

Riveted in the metal sheath and solid lid profile (secure against tearing out)



All riveted joints Realised with solid rivets



Ergonomic ZARGES comfort fasteners

Width 54 mm, optimum ergonomics and service life many times longer plus high load bearing capacity



**Ergonomic ZARGES Comfort** sprung drop handles

With return spring (stainless steel) and plastic sheathing



Additional bracing

comprised of stable aluminium profiles for K 470 from external dimensions 1,200 mm × 800 mm on base plate and lid plate



Stacking corners

Made of cast aluminium



2 load-bearing lid straps

Ends sealed to prevent fraying. No ripping out when highly stressed. Secured with special rivets (over-large head)



Hinged catch/hook made from aluminium/stainless steel

Corrosion resistance, prepared for lead seal, plug lock and shackle lock, up to shackle thickness 6 mm and latch retaining spring



(Depending on the size)

All-round beading and corner beading for reinforcement

ZARGES



High-strength, smooth and visually attractive welding points in accordance with DIN ISO 4063. Gap-free load-bearing overlap joint

of the cover sheet



High-performance flash butt welding process

In accordance with DIN EN ISO 4063. This complex production process provides high stability and torsional rigidity



Made of solid profiles, joint fully welded with sheet metal and permanently connected by high-strength form closure