

Multicore Cable

Miniature - Screened

PRO-POWER
Quality Cables



Specifications:

| | |
|-------------------------------|-------------------------|
| Voltage rating | : 440V ac. |
| Conductor area (CSA) | : 0.22mm ² . |
| Maximum operating temperature | : 70°C. |
| Sheath colour | : Grey. |
| Primary insulation material | : PVC. |
| Secondary insulation material | : PVC. |
| Conductor make-up | : 7/0.2mm. |
| Secondary insulation colour | : Grey. |

Specification Table

| Description | Number of Cores | External Diameter | Primary Screen Type | Standard | Conductor Material | Core Colour | Part Number |
|---------------------------------------|-----------------|-------------------|-----------------------------|-----------------------|--------------------|-------------|-------------|
| Cable, Screen, 12 Core, 7/0.2mm, 25M | 12 | 7.2 | Tinned Annealed Copper Wire | DEF STAN 61-12 Part 4 | Tinned Copper | Grey | 7000113 |
| Cable, Screen, 12 Core, 7/0.2mm, 100M | | 6.8 | | | | | 7001944 |
| Cable, Screen, 20 Core, 7/0.2mm, 25M | 20 | 8.6 | Tinned Copper Braid | BS6746 | | White/Blue | 860087 25M |
| Cable, Screen, 20 Core, 7/0.2mm, 100M | | | | | | | 860087 100M |

Dimensions : Millimetres

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-Power is the registered trademark of the Group. © Premier Farnell plc 2009.

<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>

PRO-POWER
Quality Cables