



## TEMPERATURE DIFFERENCE MEASUREMENT AS WELL!

New! TK 2002, simplicity with 2 inputs!

The TK 2002 is a 2-input, K-thermocouple thermometer equipped with a HOLD function.

Technical specifications:

- Measurement range:  $-50\text{ }^{\circ}\text{C}$  to  $1,000\text{ }^{\circ}\text{C}$
- Resolution:  $0.1$  or  $1\text{ }^{\circ}\text{C}$
- Accuracy:  $-50\text{ }^{\circ}\text{C}$  to  $0\text{ }^{\circ}\text{C}$ :  $\pm 1\text{ }^{\circ}\text{C}$  and  $0$  to  $1,000\text{ }^{\circ}\text{C}$ :  $\pm 1.5\% \pm 0.5\text{ }^{\circ}\text{C}$
- Display: 2,000 points
- Dimensions:  $63 \times 163 \times 37.5\text{ mm}$
- Weight: 200 g

State of delivery: delivered with 2 flexible K-thermocouple sensors for measurements from  $-40\text{ }^{\circ}\text{C}$  to  $+200\text{ }^{\circ}\text{C}$

environmental testing & measurement > thermometer > with K-type thermocouple



## NEW!

Simple temperature testing in all circumstances!

The TK 2000 is a 1-input, K-thermocouple thermometer equipped with a HOLD function:

Technical specifications:

- Measurement range:  $-50\text{ }^{\circ}\text{C}$  to  $1,000\text{ }^{\circ}\text{C}$
- Resolution:  $0.1$  or  $1\text{ }^{\circ}\text{C}$
- Accuracy:  $-50\text{ }^{\circ}\text{C}$  to  $0\text{ }^{\circ}\text{C}$ :  $\pm 1\text{ }^{\circ}\text{C}$  and  $0$  to  $1,000\text{ }^{\circ}\text{C}$ :  $\pm 1.5\% \pm 0.5\text{ }^{\circ}\text{C}$
- Display: 2,000 counts
- Dimensions  $63 \times 163 \times 37.5\text{ mm}$
- Weight: 200 g

State of delivery: delivered with 1 flexible K-thermocouple sensor for measurements from  $-40\text{ }^{\circ}\text{C}$  to  $+200\text{ }^{\circ}\text{C}$