

unimec technical specifications

	Low Temperature Versions		High Temperature Versions	
	Silver	Gold	Silver	Gold
Electrical Specifications				
Contact resistance	Max. 100 mΩ (initially)			
Insulation resistance	>10MΩ			
Recommended load	min. 0.5 mA	0 mA	0.5 mA	0 mA
	max. 250 mA - 120 V - 9W AC - 6W DC			
Max. current in non switching state	0.5 A			
Contact bounce	Max. 10mS			
Dielectric strength between adjacent contacts	1000 V for 2 min.			
Insulation resistance between adjacent contacts	5 X 10 ¹³ Ω			
Capacitance between adjacent contacts	0.5 pF			
Mechanical Specifications				
Standard actuation force (switch)	typ 2.5N			
Max. actuation force without cap	100N for 10 sec.			
Key travel (switch)	1.8 mm			
Life time	Momentary 1.500.000 cycles		Momentary >10.000.000 cycles	
	Alternate 500.000 cycles		Alternate 5.000.000 cycles	
Temperature Range				
Working temperature	Min. -40°C Max. +75°C		Min. -40°C Max. +160°C	
Storage temperature	Min. -65°C Max. +85°C		Min. -65°C Max. +160°C	
Soldering IEC 68-2-20	Wave - max. 260°C for max. 10 Sec., please refer to usage guidelines			
	Soldering iron - max. 350°C for max. 3 Sec. Flux tight.			
Environmental Endurance IEC 68-2-3				
Temperature	+40°C			
Humidity	93% RH			
Duration	56 Days			
Sealing IEC 529	IP-54			
Cleaning	Standard methods such as freon,, water and soap (not immersed)			
Material Specifications - Switches				
Housing and actuator	Glass fiber filled Polycarbonate UL94V1		LCP UL94V0	
Switch spring	Stainless steel			
Key spring	Stainless steel			
Latch pin	Stainless steel			
Fixed contact	SNCU + 2μNi + 3μAG	SNCU + 2μNi + 3μAU	SNCU + 2μNi + 3μAG	SNCU + 2μNi + 3μAU
Moving contact	BeCu + 3μAG	BeCu + 3μAG + 3μAU	BeCu + 3μAG	BeCu + 3μAG + 3μAU
Contact lubricant	Special protective lubricant Klüber Barrierta I EL Fluid			
Material Specifications - Caps & Bezels	ABS UL94V1			
Temperature limit	Max. +65°C			

Specifications are subject to change without notice

unimec LEDs

** Pulse width 1ms Duty cycle 1:5

*** I_F = 50mA

**** Luminous Flux mlm

Part Nos.	16920/16921			16922			16923			16924			
	G	Y	R	G	Y	R	G	Y	R	G	Y	R	
Absolute Maximum Ratings (Ta=25°C)													
Power	100	100	100	135	135	135	70	60	60	300	300	300	
Current forward	30	30	30	30	30	30	20	20	20	75	90	90	
Forward peak current	50	50	50	90	90	90	60**	60**	60**	2	2.5	2.5	
Voltage reverse	5	5	5	5	5	5	3	3	3	5	5	5	
Operating temperature	-25 - +100			-55 - +100			-25 - +85			-55 - +100			
Storage temperature	-25 - +100			-55 - +100			-30 - +100			-55 - +100			
Soldering temperature	+ 245 for max. 3 sec.			+300 for max. 3 sec.			260 for max. 5 sec.			300 for max. 3 sec.			
Electrical-Optical Characteristics (Ta=25°C)													
Voltage forward	Typ. V	2.0	2.0	2.0	2.1	2.2	2.3	2.1	2.1	2.0	2.4***	2.4***	2.4***
	Max. V	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.8***	3.8***	3.8***
Current reverse	μA	100	100	100	100	100	100	10	10	10	10	10	10
Wave length	nm	560	590	660	565	585	635	563	585	650	565	586	635
Spread	Δ nm	10	10	10	10	10	10	40	40	40	25	45	45
Spread angle	degree	20	20	20	45	45	45	45	45	45	55	30	55
Luminous Intensity	Min. mcd	1	1	0.8	1.5	2.5	2.5	9.0	5.6	5.6	100****	100****	100****
	Typ. mcd	2	3	1.6	2.5	3.0	5.0	25	16	16	160****	160****	160****
Orientation	The longer pin is the anode., the shorter is the cathode.												