

SEALING BOOTS













150 211

Available on models with threaded bushing

These silicone boots provide protection against water, dust and grit. On toggle versions, they also prevent ice from blocking lever action. They are compatible with frontal sealing options (K and X408).

A sealing ring is standard supplied with each boot (O-ring or washer)

Temperature range : -40°C to +85°C.

	SERIES	NUT FINISH	BLACK BOOTS
For bushings $\varnothing 4 \times 0,70$ (.157 x 0,70) 	9500	Nickel plated Matt black	U1829 U1831
For bushings $\varnothing 6 \times 0,75$ (.236 x 0,75)			
Knurled nut $\varnothing 12$ mm (472) 	5500	Nickel plated Matt black	U1341 U1343
Hex nut 11 mm (.433) across flats 	5500	Nickel plated Matt black	U1302 U1304
For bushings $\varnothing 6,35-40NS$ (1/4-40NS)			
Knurled nut $\varnothing 12$ mm (472) 	5000 } 11000 }	Nickel plated Matt black	U1331 U1333
Hex nut 11 mm (.433) across flats 	5000 } 11000 }	Nickel plated Matt black	U1229 U1231
Knurled nut $\varnothing 12$ mm (472) 	18000-8000 } 9000-13000 }	Nickel plated Matt black	U1401 U1403
Hex nut 11 mm (.433) across flats 	18000-8000 } 9000-13000 }	Nickel plated Matt black	U1318 U1320
For bushings $\varnothing 10 \times 0,75$ (.393 x 0,75)			
Knurled nut $\varnothing 18$ mm (708) 	10600	Nickel plated Matt black	U1612 U1614
Knurled nut $\varnothing 18$ mm (.708) 	10400	Nickel plated Matt black	U1624 U1626
For bushings $\varnothing 11,9-32NS$ (15/32-32NS)			
Hex nut 17 mm (669) across flats 	12000	Nickel plated Matt black	U1031 U1024
Hex nut 17 mm (669) across flats 	12000	Nickel plated Matt black	U1600 U1602
Hex nut 17 mm (669) across flats 	13000X778 } 13000X768 }	Nickel plated Matt black	U589 U590