

8413 Non-Paired - Two-Conductor, Low-Impedance Cable



Description:

24 AWG stranded (45x40) TC alloy conductors, EPDM rubber insulation, conductive textile wrap (100% coverage), TC braid shield (56% coverage), cotton spiral, EPDM jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	2
Total Number of Conductors	2
AWG	24
Stranding	45x40
Conductor Diameter	.024 in.
Conductor Material	Tinned Copper Alloy

INSULATION:

Insulation Material	EPDM - Ethylene Propylene Diene Monomer Rubber
Nom. Insulation Wall Thickness	.016 in.
Insulation Diameter	.065 in.

OVERALL CABLING:

Overall Cabling Color Code Chart :

Number	Color	Number	Color
1	White	2	Black

OUTER SHIELD:

Outer Shield Type	Tape/Braid/Spiral Serve
-------------------	-------------------------

Outer Shield Material :

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1		Tape	Conductive Textile	100
2		Braid	TC - Tinned Copper	56
3		Spiral Serve	Cotton	

Outer Shield % Coverage	100 %
-------------------------	-------

OUTER JACKET:

Outer Jacket Material	EPDM - Ethylene Propylene Diene Monomer Rubber
Outer Jacket Nominal Wall Thickness	.017 in.

OVERALL NOMINAL DIAMETER:

8413 Non-Paired - Two-Conductor, Low-Impedance Cable

Overall Nominal Diameter	.199 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +90°C
Non-UL Temperature Rating	90°C
Bulk Cable Weight	20.5 lbs/1000 ft.
Max. Recommended Pulling Tension	48 lbs.
Min. Bend Radius (Install)	2 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	No

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	55 Ohms
Nom. Inductance	0.19 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	30 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	55 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	28.7 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	11.38 Ohms/1000 ft
Max. Operating Voltage - Non-UL	300 V RMS
Max. Recommended Current	2.2 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8413 010100	2#24 EPDM SHLD EPDM	100	2.3	BLACK	
8413 010500	2 #24 EPDM SH EPDM	500	11.5	BLACK	
8413 010U500	2 #24 EPDM SHLD EPDM	U500	13	BLACK	

Revision Number: 2 Revision Date: 01-19-2006

8413 Non-Paired - Two-Conductor, Low-Impedance Cable

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.