



TECHNICAL CHARACTERISTICS

MATERIAL

INSULATOR: NYLON 66
 COLOR: GREEN
 METAL HOUSING: BRASS (CuZn)
 TERMINAL SCREW: STEEL ZINC PLATING "-" SLOT TYPE
 WIRE GUARD: PhBz TIN PLATED

ENVIRONMENTAL

OPERATING TEMPERATURE: -30 UP TO 105°C
 FLAMABILITY RATING: UL94-V0
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL

cULus	VDE
CURRENT RATING: 20A	20A
WORKING VOLTAGE: 300VAC	300VAC
WITHSTANDING VOLTAGE: 1.6KV	2.5KV

MECHANICAL

SOLID WIRE: 12-24 AWG	0.34-2.5MM ²
STRANDED WIRE: 12-24 AWG	0.34-2.5MM ²
TORQUE : 5Lb.In	0.5Nm

WIRE STRIPE LENGTH: 7-8MM

SCREW: M3
 PITCH: 5.08MM

PACKAGING
 BOX

SERIE 351

CERTIFICATION



RoHS Compliant

G			
F			
E			
D			
C			
B			
A	31-OCT-07	PDF	EC
REV	DATE	FILE	BY

PROJECTION:

GENERAL TOLERANCE
 .X = +/- 0.2
 .XX = +/- 0.15

DESCRIPTION: 5.08MM GREEN PLUG VERTICAL CABLE ENTRY WITH SCREW

WERI PART NO: 691 351 500 0xx

SIZE
A4