

Clear Mechanical Oil

Product Code: CMO

PRODUCT DESCRIPTION

Clear Mechanical Oil (CMO) offers outstanding penetration characteristics with exceptional life and lubrication efficiency. It contains a clear colloidal suspension of molybdenum disulphide which enables it to be used even after the base oil has evaporated and continues to provide exceptional anti-wear properties.

CMO is available in aerosol, handy pen dispensers, pumpspray and bulk. All forms are 100% ozone friendly.

PRODUCT USE

Electrical and Electronic Equipment

As a mechanical lubricant for use on all moving parts. One brief spray of **CMO** gives extremely long term lubrication on line printers, keyboards, platens, bearings etc.

Factory and Workshop Maintenance

Interference fits, cutting oil for pipe threading, drilling and tapping, ventilators, lift gates, door locks and hinges, window pulleys and catches, corroded nuts and bolts are all rapidly freed and lubricated with **CMO**.

Food and Beverage Industry

Conveyor chains and stacking equipment subject to washing by water or steam can be efficiently lubricated with **CMO** and the almost dry lubricating film of **CMO** reduces sticking due to spilled sticky compounds.

Home and Office

Typewriters, Dictaphones, filing cabinets, sewing machines, bicycles, toys and on any item that requires a light lubricating protective film of oil.

TECHNICAL
DATA
SHEET



**Copyright
Electrolube
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Clear Mechanical Oil – Page 2

FEATURES

- * Excellent mechanical lubricant that works at both high temperatures and extremes of pressure.
- * Protects against rust by providing a barrier against condensation and oxidation.
- * Highly tenacious film which will not drain away when moving parts come to rest.
- * Highly resistant to water washing, steam cleaning and ensures long term protective film.
- * Available in aerosol form (with an extension tube to aid access to inaccessible parts), pump spray and in bulk.

TYPICAL PROPERTIES

Form:	Light Amber liquid (Bulk) Colourless liquid (Aerosol)	
	<u>Bulk</u>	<u>Aerosol/Pumpspray</u>
Density:	0.87	0.77
Flashpoint:	200°C	-48°C
Boiling Point (Solvent):		36°C
Vapour Pressure (20°C, Solvent):		400mmHg

PACKAGING

12ml Pen - Packed in 5's
200ml Aerosol
200ml Pumpspray
5 Litre Bulk

ORDER CODE

CMO12P
CMO200D
CMO200ML
CMO05L

TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

