

VINYL-INSULATED (EASY ENTRY) LIPPED BLADE TERMINALS

MAXIMUM ELECTRIC CURRENT :

22-16 A.W.G.: 19 AMPERE 16-14 A.W.G.: 27 AMPERE 12-10 A.W.G.: 48 AMPERE


MAXIMUM ELECTRICAL RATING : 75°C 600 VOLTS MAX.

INSULATION MATERIAL : VINYL

INSULATION COLOR :

22-16 A.W.G.: RED 16-14 A.W.G.: BLUE 12-10 A.W.G.: YELLOW

TERMINAL MATERIAL : COPPER



WIRE RANGE A.W.G. mm ²	ITEM NO.		DIMENSION <small>inch mm</small>								CRIMPING TOOL	Q'TY BOX
	BRAZED SEAM	BUTTED SEAM	W	F	L	E	D	d1	A	T		
22-16 A.W.G. 0.5-1.5 mm ²	LBVEB1-3	LBVE1-3	.118 3.0	.661 16.8	1.118 28.4	.441 11.2	.157 4.0	.067 1.7	.083 2.1	.030 0.75	IZUMI MODEL 34 WITH DIE INDEX COLOR : RED OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR : RED	1000
	LBVEB1-4.6	LBVE1-4.6	.181 4.6									1000
16-14 A.W.G. 1.5-2.5 mm ²	LBVEB2-3	LBVE2-3	.118 3.0	.661 16.8	1.118 28.4	.453 11.5	.177 4.5	.091 2.3	.083 2.1	.031 0.8	IZUMI MODEL 34 WITH DIE INDEX COLOR : BLUE OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR : BLUE	1000
	LBVEB2-4.6	LBVE2-4.6	.181 4.6									1000
12-10 A.W.G. 4-6 mm ²	LBVEB5-3	LBVE5-3	.118 3.0	.677 17.2	1.232 31.3	.555 14.1	.248 6.3	.134 3.4	.094 2.4	.039 1.0	IZUMI MODEL 5 WITH DIE INDEX COLOR : YELLOW OR K.S. MODEL KST2000A HRI-126 WITH DIE INDEX COLOR : YELLOW	500
	LBVEB5-4.6	LBVE5-4.6	.181 4.6									500

3667698