

RANGES AVAILABLE.

AMMETERS

1A or 5A	CT OPERATED	AC MOVING IRON
UP TO 40A	DIRECT CONNECTED	AC MOVING IRON
UP TO 0/40/80A	DIRECT CONNECTED	AC MOVING IRON
0/1mA	DIRECT CONNECTED	DC MOVING COIL
0/20mA	DIRECT CONNECTED	DC MOVING COIL
4/20mA	DIRECT CONNECTED	DC MOVING COIL

VOLTMETERS

UP TO 600V	DIRECT CONNECTED	AC MOVING IRON
60mV	SHUNT OPERATED	DC MOVING COIL

FREQUENCY METER

45/55HZ	110,230 or 380V	SELF CONTAINED TRANSDUCER
45/65HZ	DIRECT CONNECTED	

A FULL RANGE OF SCALES ARE AVAILABLE FOR THE ABOVE ITEMS. WATTMETERS, POWER FACTOR INDICATORS AND VARMETERS ARE ALSO AVAILABLE FOR USE WITH OUR RANGE OF SEPARATE TRANSDUCERS.

THE VERSATILITY OF THE PANEL FIXING SYSTEM ALLOWS THE USER TO MOUNT THE INSTRUMENT USING A "U" CLAMP OR 4 PIN FIXING ARRANGEMENT AT 57mm OR 53mm CENTRES. ALSO AN ANTI-ROTATION PIN IS INCORPORATED TO ELIMINATE ANY MOVEMENT WHEN FIXED IN THE PANEL. WITH A ROUND BARREL DIAMETER OF 55mm, THIS INSTRUMENT IS COMPATIBLE WITH ALL METERS AVAILABLE ON THE FRENCH MARKET.

