



PART NO	SCREW SIZE	A	B	C	D	E	T	H	PANEL RANGE	X MIN	Y MIN
UN/10/A/	10 AB	19.8	12.7	7.92	N/A	N/A	0.71	7.92	0.91 2.03	N/A	N/A

*No. 10 CAPTIVE NUT*

RECOMMENDED INSTALLATION TORQUE 24 Lbs/ins (2.71 N.B.)

PART NO	SCREW SIZE	A	B	C	D	E	T	H	PANEL RANGE	X MIN	Y MIN
UN/10/B/	10 AB	19.8	12.7	7.92	N/A	N/A	0.71	7.92	3.17 3.42	N/A	N/A

MATERIAL CARBON STEEL CS 60/70	TOLERANCES 2 PLACES DECIMALS $\pm .015"$ 3 PLACES DECIMALS $\pm .005"$			SCALE N.T.S.
TREATMENT HARDEN & TEMPER	DRAWN S.A.F.	APPROVED L.W.F.	ISSUE 1	DATE 7/7/83
FINISH OIL . CODE O. ZINC / PASSIVATED . CODE ZP.	TITLE CAPTIVE "U" NUT.			
[REDACTED]	DRAWING No: 1) DA/UN/10/A/-      2) DA/UN/10/B/-			