## **ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION**

	rt Number: 1179L ge 1 of 1 Pages		Issue: Issue Date: Effective Date:	1 1/5/2009 1/5/2009
Α.	Construction 1) Component 1 a) Conductor b) Insulation (1) Color Code           Cond         Color           1         BLACK           2         RED           3         WHITE	9 X 1 COND 22 (7/30) AWG TC 0.010" Wall, Nom. Low Smoke Z Alpha Wire Company Color Code Cond Color 4 GREEN 5 ORANGE 6 BLUE		
	<ol> <li>Cable Assembly         <ul> <li>Twists:</li> <li>Core Wrap</li> </ul> </li> <li>Jacket         <ul> <li>Color(s)</li> <li>Print</li> </ul> </li> </ol>	9 Components Cabled 4.8 Twists/foot (min) Clear Mylar Tape, 25% Overlap, 0.032" Wall, Nom.,Low Smoke Z SLATE ALPHA WIRE-* P/N 1179L 9C 2 75C (UL) TYPE CM OR 75C C(L * = Factory Code	ero Halogen (LSZH) 2 AWG	0.248 (0.262 Max.)
З.	Industry Approvals			
	1) UL	CM	75°C	
	2) CSA International	FT4 C(UL) TYPE CMG	75°C	
	<ul><li>3) Other</li><li>4) EU Directive 2002/95/EC(Ro</li></ul>	REACH Regulation (EC 1907/20 HS): All materials used in the manufa 2002/95/EU regarding the restrict	06) cture of this part are tion of use of certain	hazardous substances in
		electrical and electronic equipme Date of Manufacture.	ent. Consult Alpha W	Are's web site for compliance
С.	Physical & Mechanical Propert			
	1) Temperature Range	-20 to 75°C		
	<ol> <li>Bend Radius</li> <li>Pull Tension</li> </ol>	10X Cable Diameter		
D.	Electrical Properties	49 Lbs, Maximum (For Engineering purposes only	)	
	1) Voltage Rating	300 V <sub>RMS</sub>	,	
	2) Inductance	0.17 µH/ft, Nominal		
E.	3) Conductor DCR Other	16.4 Ω/1000ft @20°C, Nominal		
	<ol> <li>Packaging         <ul> <li>Bulk(Made-to-order)</li> </ul> </li> <li>Notes:             <ul> <li>Flammability - Passes II</li> </ul> </li> </ol>	Passes IEC 60754-1 and 60754-2		

described nerein are subject to errors or omissions and to changes without notice, and the issuing or such mormation and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure