

Adhesive Cable Clips

- Strong self adhesive fixing


Material

Nylon 6.6 with adhesive tape.

Service Temperature

-20°C to +80°C.

Cable Diameter mm	Base Dimensions (W x H) mm	Packed	ORDER CODE
4	15.9 x 15.9	100	1426
8	25.4 x 25.4	100	1427
14	31.8 x 31.8	50	1850



Size	Diameter mm	Width mm	Screw Hole Diameter mm	Packed	ORDER CODE
1	3.0	9.5	5.2	100	1860
2	6.0	9.5	5.2	100	1861
3	7.5	9.5	5.2	100	1862
4	9.0	9.5	5.2	100	1863
5	11.0	9.5	5.2	100	1864
6	12.5	9.5	5.2	100	1865
7	16.0	12.7	5.2	50	1866
8	20.0	12.7	5.2	50	1867
9	25.0	12.7	5.2	50	1868
10	34.0	12.7	5.2	50	1869

P-Clips

- Secure fixing device for looms and conduits
- Screw fixing
- 10 sizes from 3.0mm to 34.0mm diameter

Material

Nylon 6.6.

Standard Colour

Black.

Service Temperature

-20°C to +85°C.

Approvals

UL file no. E97707.




Perforated Betastrip

- Suitable for fixing cables and pipes to cable tray or other surfaces
- Pre-punched – no drilling required
- Polyester coated aluminium
- 125kg breaking load

Material

99% Aluminium strip with stoved polyester resin.

Size	Width mm	Packed m	ORDER CODE Grey	ORDER CODE Orange
19		5 x 10	0413	0416



Size	Width mm	Packed m	ORDER CODE Black	Packed m	ORDER CODE Orange
4		2 x 50	0404	–	–
8		2 x 25	0411	–	–
12		2 x 25	0412	2 x 2.5	0414
19		50 x 2	0408	1 x 2	0415



Plain Betastrip

- Heavy duty, insulated strapping
- Corrosion resistant aluminium

Material

99% Aluminium strip PPVCcoated.

Service Temperature

-15°C to +50°C.

Grommet Strip

- Stops chafing on panel openings
- Suitable for plate thicknesses from 1.0mm to 6.5mm

Material

LDPE natural.

Service Temperature

-50°C to +50°C.



Size	Plate Thickness mm	swg	Minimum Corner Radius mm	Minimum Aperture Diameter mm	Packed m	ORDER CODE
2	1.0 - 1.1	up to 18	4	22	25	0494
3	1.5 - 2.0	17 - 14	5	25	25	0495
4	2.5 - 3.3	13 - 10	6	30	25	0496
5	4.0 - 4.9	–	8	36	25	0497
6	4.5 - 6.5	–	8.5	45	25	0498