



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

| REVISIONS | | DOC. NO. | SPC-F005 | * Effective: | 12/21/98 | * DCP No: | 680 | |
|-----------|-----|-------------|----------|--------------|----------|-----------|--------|---------|
| DCP # | REV | DESCRIPTION | DRAWN | DATE | CHECKD | DATE | APPRVD | DATE |
| 615 | A | RELEASED | JMM | 5/9/01 | JC | 9/4/01 | DJC | 9/21/01 |



IC Cap

NOTES:

1. Jacket Mat'l: Red Extra Flexible Silicone
 2. Conductor Size: 0.75mm²
 3. Max Current: 12 Amps
 4. Internal Resistance: 25 milliohms
 5. Body Mat'l: Polyamide (Nylon)
 6. Plug Mat'l: Bronze and Brass Nickel Plated
 7. Operating Temp.: -20°C ~ 80°C
 8. IEC61010 Ratings: 1000 V CAT III
- Reinforced or Double Insulation



DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL. THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.



| | | | |
|---|---------|--|---------------|
| UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY. | | DRAWING TITLE: 4mm Contact Tip Probe to Right-Angle Plug | |
| DRAWN BY: | DATE: | SIZE | DWG. NO. |
| Jeff McVicker | 5/9/01 | A | 76-048 |
| CHECKED BY: | DATE: | ELECTRONIC FILE | REV |
| JOHN COLE | 9/4/01 | 16F7717.dwg | A |
| APPROVED BY: | DATE: | SCALE: | NTS |
| Daniel Carey | 9/21/01 | U.O.M.: INCHES [cm] | SHEET: 1 OF 1 |