


,3182 EXP



- * FOR HOUSING SENSITIVE ELECTRONIC ASSEMBLIES, PNEUMATIC, HYDRAULIC AND FLEC TRICAL DEVICES IN COMMERCIAL AND INDUSTRIAL ENVIRONMENTS PROVIDING EFFECTIVE SHIELDING OF EMI & RFL
- * DESIGNED TO IP 65 OF IEC 529 AND NEMA 4 (DUST AND HOSEPROOF).
- * WALL MOUNTING HOLES AND LID FIXING SCREWS ARE OUTSIDE THE SEALING AREA THUS PREVENTING THE INGRESS OF MOISTURE AND DUST.
- * THE LID INCORPORATES A RECESSED NEOPRENE GASKET.
- * BOSSES ON INTERNAL BASE FOR FIXING PCB'S HORIZONTALLY OR CONNECTION OF EARTH GROUNDING, TERMINALS, ETC.
- * INTERNAL GUIDE SLOTS FOR MOUNTING PCB ASSEMBLIES VERTICALLY
- * SCREWS HOLES FOR LID MOUNTING ARE ROLL THREADED.
- * CAPTIVE, RECESSED LID SCREWS.

SPECIFICATIONS:

* BOX AND LID: ALUMINIUM ALLOY ADC-10 TO JAPAN INDUSTRIAL STANDARD (JIS) IN NATURAL FINISH.

FINISHES AVAILABLE:

- * PAINTED, BLACK.
- * EPOXY COATED, BLACK.

16-AUG-1999 05:59



