



Model No.	POS.1	POS.2	POS.3
1MS5	ON	OFF	MOM
Term. Comm.	2-3	OPEN	2-1
SCHEMATIC			

SWITCH FUNCTION

PANEL MOUNTING

SOLDER LUG

SPECIFICATIONS

ELECTRICAL LIFE: 40,000 make-and-break cycles at full load.
CONTACT RESISTANCE: 10mΩ max. initial @ 2-4VDC
 100mA for both silver and gold plated contacts.
INSULATION RESISTANCE: 1,000MΩ min.
DIELECTRIC STRENGTH: 1,000 V RMS@sea level.
OPERATING TEMPERATURE: -30° C to 85° C.

MATERIALS

CASE: Diallyl phthalate (DAP) (UL94v-0).
ACTUATOR: Brass, chrome plated.
BUSHING: Brass, nickel plated.
HOUSING: Stainless Steel.
TERMINAL/CONTACT: Silver or gold plated.

RATING :

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)
 Q : 2Amps @250VAC
 5Amps @120 VAC or 28 VDC

德利威電子股份有限公司
DAILYWELL ELECTRONICS CO.,LTD.

1	符號	原尺寸	修改後尺寸	變更日期	SCALE (比例): 3:2	TITLE 圖名	Miniature Toggle Switches	SIZE 圖紙	A4
2	(A)				TOLERANCE (公差): 0.00 mm ± 0.25mm	DWG NO. 圖號	1MS5T1B1M1RE	UNIT 單位	inch mm
3	(B)				0.0 mm ± 0.40mm	REV. 版本	A	DATA 日期	MAY - 26 - 2003
4	(C)				ANGULAR : ± 2.54 mm	CHECKED BY 審核	JACK	SHEET 張數	1 of 1
5	(D)				FILE NAME : 1MSP0380	DRAWN BY 製圖		BLUE	
	(E)								