



- Signal beacon for traffic light combinations
- High light intensity thanks to reflector (accessory)
- High protection rating IP 65 for indoor and outdoor use
- Also with two bulb sockets for uniform safety, even in the case of bulb failure
- Practical fixing bow for one, two or three signal beacons
- With a multitude of symbols
- For underground car parks, entrances and car washes

TECHNICAL SPECIFICATIONS:

Dimensions (Diameter x Height): 150 mm x 147 mm
 Housing: ABS, high impact, grey
 Dome: Polycarbonate, transparent
 Socket: E27 max. 25 W
 2 sockets E14 each with max. 15 W
 With adhesive stickers E27 max. 15 W

Fixing: Base mounting, bracket mounting
 Connection: Screw free clamp mechanism
 Contact protection according to VDE

Cable entry: From top or base with screw M 20 x 1,5 or on rear side with rubber bushing, ø 6-12 mm

Bulb not included in assembly

ORDER SPECIFICATIONS:

Permanent light 12 - 240 V ≅		Permanent light with two sockets (incl. reflector) 12 - 240 V ≅	
red	890 100 00	red	890 110 00
green	890 200 00	green	890 210 00
yellow	890 300 00	yellow	890 310 00
clear	890 400 00	clear	890 410 00
blue	890 500 00	blue	890 510 00

ACCESSORIES:

Additional reflector für 890 X00 00	975 890 02
Connecting grommet	975 890 25
Fixing bow with mounting material, for one beacon	975 890 19
Fixing bow with mounting material, for two beacons	975 890 21
Fixing bow with mounting material, for three beacons	975 890 22
Bulb E27, 230 V ≅ / 25 W	955 890 68
Bulb E27, 115 V ~ / 25 W	955 890 67
Bulb E27, 24 V ≅ / 25 W	955 890 55
Bulb E14, 230 V ≅ / 15 W	955 890 38

ADHESIVE STICKERS:

→	975 890 52	BETRIEB	975 890 57
STOP	975 890 53	STÖRUNG	975 890 58
START	975 890 54		
KEIN ZUTRITT	975 890 56		
ZUTRITT	975 890 55		

Fully captioned beacon on request.
 Further symbols on request.

890 with fixing bow (accessory)



890 with adhesive sticker (accessory)



Permanent beacon with two sockets

TECHNICAL DIAGRAMS

see page 131

