



**PANEL MOUNTING**

**SOLDER LUG**

Model No.	POS.1	POS.2	POS.3
1MS4	MOM	OFF	MOM
Term. Comm.	2-3	OPEN	2-1
SCHEMATIC			

**SWITCH FUNCTION**

**RATING :**

R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)  
 Q : 2Amps @250VAC  
 5Amps @120 VAC or 28 VDC

**德利威電子股份有限公司**  
**DAILYWELL ELECTRONICS CO.,LTD.**

**SPECIFICATIONS**  
**ELECTRICAL LIFE:** 40,000 make-and-break cycles at full load.  
**CONTACT RESISTANCE:** 10m Ω max. initial @ 2-4VDC  
 100mA for both silver and gold plated contacts.  
**INSULATION RESISTANCE:** 1,000M Ω min.  
**DIELECTRIC STRENGTH:** 1,000 V RMS@sea level.  
**OPERATING TEMPERATURE:** -30 ° C to 85 ° C.

**MATERIALS**  
**CASE:** Dially phthalate (DAP) (UL94v-0).  
**ACTUATOR:** Brass,chrome plated.  
**BUSHING:** Brass,nickel plated.  
**HOUSING:** Stainless Steel.  
**TERMINAL/CONTACT:** Silver or gold plated.

符號	原尺寸	修改後尺寸	變更日期	SCALE (比例) : 3 : 2	TITLE 圖名	Miniature Toggle Switches	SIZE 圖紙	A4		
1 (A)				TOLERANCE (公差) : 0.00 mm ± 0.25mm 0.0 mm ± 0.40mm ANGULAR : ± 2.54 mm FILE NAME : 1MSP0348	DWG NO.	1MS4T1B1M1RE	UNIT 單位	inch		
2 (B)					REV. 版本	A	DATA 日期	JAN - 21 - 2003	SHEET 張數	1 of 1
3 (C)					CHECKED BY 審核	JACK	DRAWN BY 製圖	BLUE		
4 (D)										
5 (E)										