







1. MATERIAL
   HOUSING: PBT, GLASS FILLED, UL RATED 94V-0, BLACK.
   FRONT SHELL: CARBON STEEL.
   BOARDLOCKS AND INSERTS: BRASS
   CONTACTS: PHOSPHOR BRONZE
2. FINISH
   FRONT SHELL: TIN PLATED.
   CONTACTS: GOLD FLASH OVER 2.54µm [.000100] MIN NICKEL ON ENTIRE CONTACT AREA.
   BOARDLOCKS AND INSERTS: NICKEL PLATED.
3. ELECTRICAL SPECIFICATIONS:
   20 OHMS AT 30 MHz.
   30 OHMS AT 50 MHz.
   50 OHMS AT 100 MHz.

4v SCI, 56-424-001 AND DATE CODE MARKED ON THIS SURFACE.



P.C. BOARD MOUNTING DIMENSIONS

4	REVISED PER 99146	04 NOV 99	DG	GL	
P	LTR	REVISION RECORD	DATE	DRN	APVD

DRN D.GELTZ 04 NOV 99
CHK G.LURIE 04 NOV 99
APVD G.LURIE 04 NOV 99
MATERIAL -
HEAT TREAT -

SPECTRUM CONTROL, INC.
INTERCONNECT PRODUCTS DIVISION
FAIRVIEW, PENNSYLVANIA

TITLE RECEPTACLE ASSEMBLY, 25 POSITION, RIGHT ANGLE, FERRITE

SCALE 4:1 | SIZE A1 | DRAWING NO 56-424-001 | SHEET 1 OF 1 | REV 4

DIMENSIONS ARE IN INCHES [MILLIMETERS]
TOLERANCES UNLESS OTHERWISE SPECIFIED
.XX ±0.13 [.005]
.XXX ±0.025 [.001]
ANGLES ±1°
SURFACE TEXTURE √

THIS DRAWING IS A CONTROLLED DOCUMENT.

PART NO 56-424-001

04-NOV-99 1647402 geltz /as/files/work/dsm/99146