




Features:

- This series offers a grey non marking rubber tyre on a black nylon centre including threadguards which is available with pain bore.


The wheel can be fitted in the following castor housings:

- Top plate swivel, fixed and swivel with food brake.
- Threaded stem swivel and threaded stem with foot brake.


Swivel Castor




Fixed Castor




Threaded Stem Castor



**Swivel Castor
with Foot Brake**



**Threaded Stem Castor
with Foot Brake**



Dimensions : Millimetres

Recommended uses:

This wheel type is recommended for light duty applications.

Specification:

In accordance with ISO 2175. Defines castor and/or wheel application appropriate with environmental conditions - load, speed of use, temperature, floor condition and cycle time. For further advice and details please consult your supplier as it is sometimes necessary to select a wheel or castor with a specification several times greater than conditions appear to warrant, in order to achieve a particular performance criteria.

Specification Table

Wheel Diameter (D)	Thread Width (b)	Overall Height (H)	Plate Dimensions (A x B)	Hole Spacing (a x b)	Hole Width (e)	Offset (E)	Carrying Capacity (kg)	Pedal Length (O)	Stem Diameter (C)	Stem Length (F)	Plate Diameter (G)	Part Number
50*	20	68	55 x 55	40 x 40	6	25	35	-	-	-	-	37 4101
60*	24	85	60 x 60	45 x 45		21	50	-	-	-	-	37 4102
80*		106				55	-	-	-	-	37 4103	
100*		121					-	-	-	-	37 4104	
50**	20	68	55 x 55	40 x 40		-	35	-	-	-	-	37 5101
60**	24	85	60 x 60	45 x 45		-	50	-	-	-	-	37 5102
100**		121				-	55	-	-	-	-	37 5104
50***	20	66	-	-	-	25	35	-	8M	15	35	37 6101
60***	24	83	-	-	-	21	50	-	12M	25	41	37 6102
80***		104	-	-	-	25	55	-				37 6103
100***		121	-	-	-	32		-				37 6104
50*	20	68	55 x 55	40 x 40	6	25	35	76	-	-	-	37 8101
60*	24	85	60 x 60	45 x 45		21	50	84	-	-	-	37 8102
80*		106				25	55	91	-	-	-	37 8103
50***	20	66	-	-	-		35	76	8M	15	35	37 9101
60***	24	83	-	-	-	21	50	84	12M	25	41	37 9102
80***		104	-	-	-	25	55	91				37 9103
100***		121	-	-	-	32		95				37 9104

* Swivel Top

** Fixed Top

*** Swivel

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2009.