



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
 5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. JIS H 3250, C 2700

1. CRIMPED FERRULE
 HEX CRIMP SIZE .255"
 2. CONTACT PIN TO SOLDER

11	NUT	NOTE 1	NOTE 3	1	B5291-14
10	FERRULE	NOTE 6	NOTE 3	1	FR-75/66X127
9	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
8	SPRING	SK5	NOTE 4	2	B50000-6
7	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
6	GASKET	RUBBER	RED	1	GS-115/8X15
5	CONTACT PIN	NOTE 1	NOTE 5	1	B5091-6-75-B
4	INSULATOR	DELTRIN	NATURAL	1	B5091-5-75
3	BARREL	NOTE 1	NOTE 3	1	B5091-3-56/39
2	HOUSING	NOTE 1	NOTE 3	1	B5091-2
1	SHELL	NOTE 1	NOTE 3	1	B50000-1-B
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS				PART NO. B1112A1-ND3G-3-75	
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE
0.5-6	= ±0.2				10-11-01'
6-30	= ±0.4			CHECKED	DATE
30-120	= ±0.6				10-11-01'
120-315	= ±1			DRAWN	DATE
315-1000	= ±1.6				10-11-01'
1000-2000	= ±2.4			FILE NO.	

Amphenol	
TITLE BNC R/A CRIMP PLUG	
DRAWING NO. KJ-B1112A1-ND3G-59U-75	
ITEM NO.	