



RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS.
2. BREAKAWY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
3. .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL.
4. .000100-.000200 BRIGHT TIN OVER .000050 NICKEL.
5. PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
6. HOUSING MATERIAL: FLAME RETARDANT THERMOPLASTIC; COLOR-BLACK. POSTS: PHOS BRONZE
7. .000100-.000200 MATTE TIN OVER .000050 NICKEL.

3.984	3.900	39	40	9-103323-0
3.884	3.800	38	39	8-103328-9
3.784	3.700	37	38	8-103328-8
3.684	3.600	36	37	8-103328-7
3.584	3.500	35	36	8-103328-6
3.484	3.400	34	35	8-103328-5
3.384	3.300	33	34	8-103328-4
3.284	3.200	32	33	8-103328-3
3.184	3.100	31	32	8-103328-2
3.084	3.000	30	31	8-103328-1
2.984	2.900	29	30	8-103328-0
2.884	2.800	28	29	7-103323-9
2.784	2.700	27	28	7-103323-8
2.684	2.600	26	27	7-103323-7
2.584	2.500	25	26	7-103323-6
2.484	2.400	24	25	7-103323-5
2.384	2.300	23	24	7-103323-4
2.284	2.200	22	23	7-103323-3
2.184	2.100	21	22	7-103323-2
2.084	2.000	20	21	7-103323-1
1.984	1.900	19	20	7-103323-0
1.884	1.800	18	19	6-103323-9
1.784	1.700	17	18	6-103323-8
1.684	1.600	16	17	6-103323-7
1.584	1.500	15	16	6-103323-6
1.484	1.400	14	15	6-103323-5
1.384	1.300	13	14	6-103323-4
1.284	1.200	12	13	6-103323-3
1.184	1.100	11	12	6-103323-2
1.084	1.000	10	11	6-103323-1
.984	.900	9	10	6-103323-0
.884	.800	8	9	5-103323-9
.784	.700	7	8	5-103323-8
.684	.600	6	7	5-103323-7
.584	.500	5	6	5-103323-6
.484	.400	4	5	5-103323-5
.384	.300	3	4	5-103323-4
.284	.200	2	3	5-103323-3
.184	.100	1	2	5-103323-2
.084	—	—	1	5-103323-1

.184	.100	1	2	4-103323-2
3.984	3.900	39	40	4-103323-1
3.984	3.900	39	40	4-103323-0
3.884	3.800	38	39	3-103323-9
3.784	3.700	37	38	3-103323-8
3.684	3.600	36	37	3-103323-7
3.584	3.500	35	36	3-103323-6
3.484	3.400	34	35	3-103323-5
3.384	3.300	33	34	3-103323-4
3.284	3.200	32	33	3-103323-3
3.184	3.100	31	32	3-103323-2
3.084	3.000	30	31	3-103323-1
2.984	2.900	29	30	3-103323-0
2.884	2.800	28	29	2-103323-9
2.784	2.700	27	28	2-103323-8
2.684	2.600	26	27	2-103323-7
2.584	2.500	25	26	2-103323-6
2.484	2.400	24	25	2-103323-5
2.384	2.300	23	24	2-103323-4
2.284	2.200	22	23	2-103323-3
2.184	2.100	21	22	2-103323-2
2.084	2.000	20	21	2-103323-1
1.984	1.900	19	20	2-103323-0
1.884	1.800	18	19	1-103323-9
1.784	1.700	17	18	1-103323-8
1.684	1.600	16	17	1-103323-7
1.584	1.500	15	16	1-103323-6
1.484	1.400	14	15	1-103323-5
1.384	1.300	13	14	1-103323-4
1.284	1.200	12	13	1-103323-3
1.184	1.100	11	12	1-103323-2
1.084	1.000	10	11	1-103323-1
.984	.900	9	10	1-103323-0
.884	.800	8	9	103323-9
.784	.700	7	8	103323-8
.684	.600	6	7	103323-7
.584	.500	5	6	103323-6
.484	.400	4	5	103323-5
.384	.300	3	4	103323-4
.284	.200	2	3	103323-3
.184	.100	1	2	103323-2
.084	—	—	1	103323-1

PLATING	C	B	A	NO OF POSN	PART NUMBER
---------	---	---	---	------------	-------------

PLATING	C	B	A	NO OF POSN	PART NUMBER
---------	---	---	---	------------	-------------

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PL	± .005
1 PL	± .005
2 PL	± .005
3 PL	± .005
4 PL	± .005
ANGLES	± .005
FINISH	SEE TABLE

MATERIAL: SEE TABLE

APPROVED: JOHN KNITTLE

DATE: 23NOV92

DESIGNED BY: B. FLINCHBAUGH

DATE: 23NOV92

NAME: HEADER ASSY, MOD II, BREAKAWAY, SINGLE ROW, .100, RIGHT ANGLE, WITH .025 SQUARE POSTS

SIZE: A1

SCALE: 4:1

SHEET: 1 OF 1

REV: K

DRAWING NO: 00779

DRAWING NO: 103323

CUSTOMER DRAWING